



MLFB-Ordering data: 1LE1502-3AB03-4AA4

Motor type: 1CV1310B

Client order no.:

Order no.:

Offer no.:

Remarks:

Item no.:

Consignment no.:

Project:

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N I _f /I _N	M _A /M _N T _f /T _N	M _K /M _N T _B /T _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
400	Δ	50	110.00	- / -	205.00	1488	706.0	93.3	93.4	92.8	0.84	0.80	0.71	6.5	2.3	2.7	IE1
690	Y	50	110.00	- / -	117.00	1488	706.0	93.3	93.4	92.8	0.84	0.80	0.71	6.5	2.3	2.7	IE1
460	Δ	60	127.00	- / -	200.00	1788	678.0	93.5	93.5	92.6	0.85	0.82	0.74	6.5	2.3	2.7	IE1
IM B3 / IM 1001		FS 315 S		730 kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Mechanical data

Sound pressure level 50Hz/60Hz (load)	75 dB(A) ¹⁾	75 dB(A) ¹⁾
Moment of inertia	1.90 kg m ²	
Bearing DE NDE	6319 C3	6319 C3
Relubrication interval/quantity	40 g 40 g 6000 h	
Lubricants	Esso Unirex N3	
Regreasing device	Yes (standard)	
Grease nipple	M10x1 DIN 3404 A	
Type of bearing	Locating bearing NDE	
Condensate drainage holes	Yes (standard)	
External earthing terminal	Yes (standard)	
Vibration severity grade	A	
Insulation	155(F) to 130(B)	
Duty type	S1	
Direction of rotation	bidirectional	
Frame material	cast iron	
Data of anti condensation heating	-/-	
Coating (paint finish)	Standard paint finish C2	
Color, paint shade	RAL7030	
Motor protection	(A) without (Standard)	
Method of cooling	IC411 - self ventilated, surface cooled	

Environmental conditions

Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m

Notes

I_A¹⁾ = locked rotor current / current nominal M_K/M_N = break down torque / nominal torque
M_A/M_N = locked rotor torque / torque nominal 1) Value is valid only for DOL operation with motor design IC411

Terminal box

Terminal box position	top
Material of terminal box	cast iron
Type of terminal box	TB1 Q01
Contact screw thread	M12
Max. cross-sectional area	240.0 mm ²
Cable diameter from ... to ...	38.0 mm - 45.0 mm
Cable entry	2xM63x1,5
Cable gland	2 plugs

Special design (0)



Tel: 48 0000 49 (60 Lines)

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for any damages caused by their actions. Patent, trademark, copyright or other rights of a utility model or design patent are reserved.

Weitergabe sowie Vervielfältigung, Verbreitung und/oder Bearbeitung dieses Dokuments, Verwertung und Mitteilung seines Inhaltes sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte vorbehalten. Gebrauchsmuster, Marken, Patente oder Geschmackschutzrechte sind vorbehalten.

Confidà a títol de secret d'empreses. Tots drets reservats. Comunicado como secreto empresarial. Reservados todos los derechos. Довіреність а інформації провласності нашої компанії. Всі права зарезервовані. Конфілідо como secreto de empresa. Nos reservamos todos los derechos.

Tel: 48 0000 49 (60 Lines)



DIN 332-DS M20
DIN 6885-1

Tolerance	Surface	Material	Weight	Scale
1LE1502-3AB03-4AA4	Author	Dimensional drawing		
	Creator	Maßzeichnung		
	Approval			
	Department			
	Change Order	MFB	Doc. Type	
	Doc. State	1/22/19	Item No.	Page Size A3
	Revision	Index RS	Doc. No.	1st Language en 2nd Language de
© Siemens AG 2018	Project No.	-	Ref. No.	Sheet 1 of 1