

SQDL&SQXL Series Submersible Drainage Pumps

Advantages

- ★ Longitudinally cutting shaft;
- ★ High-efficient motor with very low noise and temperature rise;
- ★ High-quality mechanical seal;
- ★ Upgraded design style and materials;
- ★ Keep same color like traditional SQD&SQX.



Comparison with Traditional type

Top cover



Stronger Pump body



More thick and zinc-plated Strainer



SQDL&SQXL

Model	Power	Outlet	Max.Flow	Max.Head	Dimensions	G.W.	20' Loading Qty		
								Single-Phase	Three-Phase
SQD1.5-12-0.25L	-	25	5	14	360×160×200	5	2647		
SQD1.5-17-0.37L	-	25	6	18	385×160×220	7	2499		
SQD1.5-25-0.55L	-	25	5	26	395×190×220	9.5	1776		
SQD3-18-0.55L	-	32	8	20	410×195×220	9.5	1715		
SQD10-12-0.55L	-	38	15	18	410×210×220	9.5	1598		
SQD15-7-0.55L	-	51	24	9	410×210×220	9.5	1598		
SQD1.5-32-0.75L	-	25	8	33	415×210×215	11.5	1806		
SQD3-24-0.75L	-	32	9	25	410×195×220	11.5	1715		
SQD8-18-0.75L	-	38	15	20	420×195×230	11	1614		
SQD10-16-0.75L	-	51	15	20	420×195×230	11	1614		
SQD15-10-0.75L	-	64	36	12	420×220×240	11.5	1363		
SQD25-6-0.75L	-	76	35	11	420×220×260	11.5	1262		
SQD30-6-0.75L	-	76	45	11	455×280×215	13.5	1103		
SQD3-30-1.1L	-	25	10	31	450×280×225	15	1070		
SQD14-16-1.1L	-	51	29	18	470×280×215	15	1069		
SQD15-14-1.1L	-	64	29	18	470×280×215	15	1069		
SQD40-6-1.1L	-	76	60	10	505×280×215	18	990		
-	SQX8-18-0.75L	38	15	20	420×195×230	10.5	1262		
-	SQX10-16-0.75L	51	15	20	420×195×230	10.5	1103		
-	SQX30-6-0.75L	76	45	11	455×280×215	13	1069		
-	SQX3-30-1.1L	25	10	31	455×280×215	12	1103		
-	SQX14-16-1.1L	51	29	18	470×280×215	15	1069		
-	SQX15-14-1.1L	64	29	18	470×280×215	15	1069		
-	SQX40-6-1.1L	76	60	10	505×280×215	17	990		
-	SQX25-12-1.5L	64	37	18	505×280×215	17	990		
-	SQX40-9-1.5L	76	61	12	530×280×215	19	990		

SQDL&SQXL Hydraulic Performance Curve

