

Jan 06, 2026




Product data sheet

HDC32511M7

Characteristics

Contactor, HDC3-2511, 220/230 V, 50/60 Hz



Main

Range of product	HDC3
Product or component type	Contactor
Contactor application	Non-reversing
Poles description	3P
[Ith] conventional free air thermal current	40 A

Complementary

Utilisation category	AC-3 AC-4
[In] rated current	25 A
[Uc] control circuit voltage	220/230 V AC 50/60 Hz
Auxiliary contact composition	1 NO + 1 NC
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	25 A at 380/400 V AC-3 18 A at 660/690 V AC-3 8.5 A at 380/400 V AC-4 4.4 A at 660/690 V AC-4
Motor power kW	11 kW at 380/400 V AC-3 15 kW at 660/690 V AC-3 5.5 kW at 380/400 V AC-4 4 kW at 660/690 V AC-4
Net weight	0.47 kg

Environment

Installation category	III
Pollution degree	3
Ambient air temperature for operation	-5...40 °C
Average ambient air temperature for operation	= 35 °C (average over 24 hours)
Ambient air temperature for storage	-25...55 °C
Operating altitude	2000 m
Standards	IEC 60947-4-1
Product certifications	CB CE SEMKO
IP degree of protection	IP20
Relative humidity	0...50 % at 0...40 °C 0...90 % at 0...20 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30 cm
Package 1 Width	30 cm
Package 1 Length	40 cm
Package 1 Weight	0.4694444444444444 kg

Offer Sustainability

Sustainable packaging	No
-----------------------	----