

SIEMENS

Data sheet for three-phase Squirrel-Cage-Motors



MLFB-Ordering data: 1LE1002-1BA22-2AA4

Motor type: 1AV1112A
Client order no.:
Order no.:
Offer no.:
Remarks:

Item no.:
Consignment no.:
Project:

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I_A/I_N I_f/I_N	M_A/M_N T_f/T_N	M_K/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
230	Δ	50	4.00	- / -	14.20	2935	13.0	83.1	82.9	80.5	0.85	0.77	0.65	8.3	3.3	4.2	IE1
400	Y	50	4.00	- / -	8.20	2935	13.0	83.1	82.9	80.5	0.85	0.77	0.65	8.3	3.3	4.2	IE1
460	Y	60	4.55	- / -	7.80	3535	12.0	84.5	84.2	82.1	0.87	0.82	0.71	9.0	3.3	4.6	IE1
IM B3 / IM 1001			FS 112 M			25 kg	IP55	IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Mechanical data		
Sound pressure level 50Hz/60Hz (load)	69 dB(A) ¹⁾	73 dB(A) ¹⁾
Moment of inertia	0.0067 kg m²	
Bearing DE NDE	6206 2Z C3	6206 2Z C3
Bearing lifetime	40000 h	
Lubricants	Esso Unirex N3	
Regreasing device	No	
Grease nipple	- / -	
Type of bearing	Preloaded bearing DE	
Condensate drainage holes	No	
External earthing terminal		
Vibration severity grade	A	
Insulation	155(F) to 130(B)	
Duty type	S1	
Direction of rotation	bidirectional	
Frame material	aluminum	
Data of anti condensation heating	-/-	
Coating (paint finish)	Standard paint finish C2	
Color, paint shade	RAL7030	
Motor protection	(A) without (Standard)	
Method of cooling	IC411 - self ventilated, surface cooled	

Environmental conditions	
Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m

Notes	
I_A/I_N = locked rotor current / current nominal	M_K/M_N = break down torque / nominal torque
M_A/M_N = locked rotor torque / torque nominal	1) Value is valid only for DOL operation with motor design IC411

Terminal box	
Terminal box position	top
Material of terminal box	Aluminium
Type of terminal box	TB1 F00
Contact screw thread	M4
Max. cross-sectional area	4.0 mm²
Cable diameter from ... to ...	11.0 mm - 21.0 mm
Cable entry	2xM32x1,5
Cable gland	2 plugs

Special design (0)


Tel: 48 0000 49 (60 Lines)

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for any damages caused by such actions. Patent, trademark, copyright or other rights of a utility model or design patent are reserved.



Weitergabe sowie Vervielfältigung, Verbreitung und/oder Bearbeitung dieses Dokuments, Verwertung und Mitteilung seines Inhaltes sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte vorbehalten, insbesondere das Urheberrecht, das Patentrecht oder das Recht der Erfindung, das Markenrecht, das Designrecht oder das Recht der Erfindung.

Confidencial e secreto. Toda revelación, comunicación o uso no autorizado de este documento, así como la explotación de su contenido y la comunicación de éste a terceros, quedan expresamente prohibidos. Los responsables serán considerados como infractores de la ley. Reservados todos los derechos. No se reservan todos los derechos.

Confidantiale en het geheim. Het openbaar maken, verspreiden of anderszins openbaar maken van de inhoud van dit document, evenals het gebruik van de inhoud van het document en het verspreiden daarvan, is uitdrukkelijk verboden. De afzender aanvaardt aansprakelijkheid voor schade van welke aard ook voortvloeiende uit het gebruik van de inhoud van het document. Alle rechten zijn voorbehouden, met name het auteursrecht, het octrooi, het merkrecht, het ontwerprecht of het recht van uitvinding.



DIN 332-DR M10
DIN 6885-1



Tel: 48 0000 49 (60 Lines)

Tolerance	Surface	Material	Weight	Scale
1LE1002-1BA22-2AA4	Author	Dimensional drawing Maßzeichnung		
	Creditor			
	Approval			
	Department			
	Change Order	MFB	Doc Type	
SIEMENS	Doc State	1/21/19	Item No	Paper Size A3
	Revision	Index	Doc No	1st Language en
				2nd Language de
© Siemens AG 2018	Project No	-	Ref No	Sheet 1 of 1