



PRODUCT-DETAILS

AF16-30-10-11

AF16-30-10-11 24-60V50/60HZ 20-60VDC
Contactor



General Information	
Extended Product Type	AF16-30-10-11
Product ID	1SBL177001R1110
EAN	3471523110618
Catalog Description	AF16-30-10-11 24-60V50/60HZ 20-60VDC Contactor
Long Description	The AF16-30-10-11 is a 3 pole - 690 V IEC or 600 UL contactor with 1 built-in auxiliary contact and screw terminals, controlling motors up to 7.5 kW / 400 V AC (AC-3) or 10 hp / 480 V UL and switching power circuits up to 30 A (AC-1) or 30 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (24-60 V 50/60 Hz and 20-60 V DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

EPLAN Data	9AAC159647_EPLAN
Data Sheet, Technical Information	1SBC100214C0202
Instructions and Manuals	1SBC101027M6801
Instructions and Manuals (Part 2)	1SAC200017M0002
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	45 mm
Product Net Depth / Length	77 mm
Product Net Height	86 mm
Product Net Weight	0.27 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	0
Number of Poles	3P
Standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-4-1
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ }^{\circ}\text{C}$ 35 A acc. to IEC 60947-5-1, $\Theta = 40\text{ }^{\circ}\text{C}$ 16 A
Rated Operational Current AC-1 (I _e)	(690 V) 40 °C 30 A (690 V) 60 °C 30 A (690 V) 70 °C 26 A
Rated Operational Current AC-3 (I _e)	(415 V) 60 °C 18 A (440 V) 60 °C 18 A (500 V) 60 °C 15 A (690 V) 60 °C 10.5 A (380 / 400 V) 60 °C 18 A (220 / 230 / 240 V) 60 °C 18 A
Rated Operational Current AC-3e (I _e)	(415 V) 60 °C 18 A (440 V) 60 °C 18 A (500 V) 60 °C 15 A (690 V) 60 °C 10.5 A (380 / 400 V) 60 °C 18 A (220 / 230 / 240 V) 60 °C 18 A
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Operational	(110 V) 1-Pole, 40 °C 20 A

Current DC-1 (I_e)

- (110 V) 1-Pole, 60 °C 20 A
- (110 V) 1-Pole, 70 °C 20 A
- (110 V) 2 Poles in Series, 40 °C 30 A
- (110 V) 2 Poles in Series, 60 °C 30 A
- (110 V) 2 Poles in Series, 70 °C 26 A
- (110 V) 3 Poles in Series, 40 °C 30 A
- (110 V) 3 Poles in Series, 60 °C 30 A
- (110 V) 3 Poles in Series, 70 °C 26 A
- (220 V) 2 Poles in Series, 40 °C 20 A
- (220 V) 2 Poles in Series, 60 °C 20 A
- (220 V) 2 Poles in Series, 70 °C 20 A
- (220 V) 3 Poles in Series, 40 °C 30 A
- (220 V) 3 Poles in Series, 60 °C 30 A
- (220 V) 3 Poles in Series, 70 °C 26 A
- (72 V) 1-Pole, 40 °C 30 A
- (72 V) 1-Pole, 60 °C 30 A
- (72 V) 1-Pole, 70 °C 26 A
- (72 V) 2 Poles in Series, 40 °C 30 A
- (72 V) 2 Poles in Series, 60 °C 30 A
- (72 V) 2 Poles in Series, 70 °C 26 A
- (72 V) 3 Poles in Series, 40 °C 30 A
- (72 V) 3 Poles in Series, 60 °C 30 A
- (72 V) 3 Poles in Series, 70 °C 26 A

Rated Operational
Current DC-3 (I_e)

- (110 V) 1-Pole, 40 °C 8 A
- (110 V) 1-Pole, 60 °C 8 A
- (110 V) 1-Pole, 70 °C 8 A
- (110 V) 2 Poles in Series, 40 °C 30 A
- (110 V) 2 Poles in Series, 60 °C 30 A
- (110 V) 2 Poles in Series, 70 °C 26 A
- (110 V) 3 Poles in Series, 40 °C 30 A
- (110 V) 3 Poles in Series, 60 °C 30 A
- (110 V) 3 Poles in Series, 70 °C 26 A
- (220 V) 2 Poles in Series, 40 °C 8 A
- (220 V) 2 Poles in Series, 60 °C 8 A
- (220 V) 2 Poles in Series, 70 °C 8 A
- (220 V) 3 Poles in Series, 40 °C 30 A
- (220 V) 3 Poles in Series, 60 °C 30 A
- (220 V) 3 Poles in Series, 70 °C 26 A
- (72 V) 1-Pole, 40 °C 30 A
- (72 V) 1-Pole, 60 °C 30 A
- (72 V) 1-Pole, 70 °C 26 A
- (72 V) 2 Poles in Series, 40 °C 30 A
- (72 V) 2 Poles in Series, 60 °C 30 A
- (72 V) 2 Poles in Series, 70 °C 26 A
- (72 V) 3 Poles in Series, 40 °C 30 A
- (72 V) 3 Poles in Series, 60 °C 30 A
- (72 V) 3 Poles in Series, 70 °C 26 A

Rated Operational
Current DC-5 (I_e)

- (110 V) 1-Pole, 40 °C 4 A
- (110 V) 1-Pole, 60 °C 4 A
- (110 V) 1-Pole, 70 °C 4 A
- (110 V) 2 Poles in Series, 40 °C 20 A
- (110 V) 2 Poles in Series, 60 °C 20 A
- (110 V) 2 Poles in Series, 70 °C 20 A
- (110 V) 3 Poles in Series, 40 °C 30 A
- (110 V) 3 Poles in Series, 60 °C 30 A
- (110 V) 3 Poles in Series, 70 °C 26 A
- (220 V) 2 Poles in Series, 40 °C 4 A
- (220 V) 2 Poles in Series, 60 °C 4 A
- (220 V) 2 Poles in Series, 70 °C 4 A
- (220 V) 3 Poles in Series, 40 °C 16 A
- (220 V) 3 Poles in Series, 60 °C 16 A
- (220 V) 3 Poles in Series, 70 °C 16 A
- (72 V) 1-Pole, 40 °C 16 A
- (72 V) 1-Pole, 60 °C 16 A
- (72 V) 1-Pole, 70 °C 16 A
- (72 V) 2 Poles in Series, 40 °C 30 A
- (72 V) 2 Poles in Series, 60 °C 30 A
- (72 V) 2 Poles in Series, 70 °C 26 A
- (72 V) 3 Poles in Series, 40 °C 30 A
- (72 V) 3 Poles in Series, 60 °C 30 A
- (72 V) 3 Poles in Series, 70 °C 26 A

Rated Operational Current DC-13 (I _e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Operational Power AC-3 (P _e)	(400 V) 7.5 kW (415 V) 9 kW (440 V) 9 kW (500 V) 9 kW (690 V) 9 kW (380 / 400 V) 7.5 kW (220 / 230 / 240 V) 4 kW
Rated Operational Power AC-3e (P _e)	(415 V) 9 kW (440 V) 9 kW (500 V) 9 kW (690 V) 9 kW (380 / 400 V) 7.5 kW (220 / 230 / 240 V) 4 kW
Rated Short-time Withstand Current Low Voltage (I _{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A for 0.1 s 140 A for 1 s 100 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 250 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 106 A
Rated Insulation Voltage (U _i)	acc. to IEC 60947-4-1 690 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-15) 1200 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour (DC-13) 900 cycles per hour
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U _c)	50 Hz 24 ... 60 V 60 Hz 24 ... 60 V DC Operation 20 ... 60 V
Power Loss	at 6 A per Pole 0.1 W at Rated Operating Conditions AC-1 per Pole 1.2 W at Rated Operating Conditions AC-3 per Pole 0.35 W
Operate Time	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M4 Screws Placed Diagonally
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 0.75 ... 6 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 4 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 4 mm ² Rigid Stranded 1/2x 1 ... 6 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ²

	Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Connecting Capacity Control Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ²
Wire Stripping Length	Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 10 mm
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Tightening Torque	Auxiliary Circuit 1.2 N·m Control Circuit 1.2 N·m Main Circuit 1.5 N·m
Terminal Type	Screw Terminals
Product Name	Block Contactor

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(600 V AC) 30 A
Horsepower Rating UL/CSA	(120 V AC) Single Phase 1-1/2 hp (200 ... 208 V AC) Three Phase 5 hp (220 ... 240 V AC) Three Phase 5 hp (240 V AC) Single Phase 3 hp (440 ... 480 V AC) Three Phase 10 hp (550 ... 600 V AC) Three Phase 15 hp
Connecting Capacity Main Circuit UL/CSA	Rigid Solid 1/2x 16-10 AWG Rigid Stranded 1/2x 16-10 AWG
Connecting Capacity Auxiliary Circuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Connecting Capacity Control Circuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 11 in·lb Control Circuit 11 in·lb Main Circuit 13 in·lb
Full Load Amps Motor Use	(120 V AC) Single Phase 20 A (200 ... 208 V AC) Three Phase 17.5 A (220 ... 240 V AC) Three Phase 15.2 A (240 V AC) Single Phase 17 A (440 ... 480 V AC) Three Phase 14 A (550 ... 600 V AC) Three Phase 17 A

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: B1 25 g Open, Shock Direction: B1 5 g Shock Direction: A 30 g Shock Direction: B2 15 g Shock Direction: C1 25 g Shock Direction: C2 25 g

Resistance to Vibrations	4g Closed Position & 2g Open position 5 ... 300 Hz
Pollution Degree	3

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Declaration	2CMT2021-006277
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	f7ff6eaf-0746-41f7-8f81-a89add39cd4b China
Simplified SCIP	ec002f2f-11b8-4c80-8d70-7fd838b2dc73 Sweden 1b4c195f-bc19-469d-b9d5-e4c5be9bcc97 Belgium 3732b39e-b39b-4943-a687-3f541333d931 Czech Republic a453984b-8a6b-4eab-9f0d-718f0dd02815 Croatia eeb611e8-e754-46de-a90d-67628e9b7cd6 Germany 69f44487-7f35-49eb-ba77-b2916e1db7b6 Spain cee654eb-bbaa-4df2-85aa-087a580a70e1 Greece 9ad84e8d-53d8-4698-8be7-d47ccc9ffcb9 Bulgaria ffbc558e-f7e6-4bad-a048-d99c6acd438d Germany 41333280-34d8-42eb-8861-8b54bc62fa74 Belgium 188b5e51-96a0-45c4-82df-6839792050df Portugal 83ad28e8-5fc3-4751-a118-cc4b28261fe0 Denmark 25f55f3e-8f32-48a9-ac05-8fd500e052f8 Germany 3b62af72-c664-40f1-8945-325c6aaa631f Sweden fd6432d9-8cb8-46df-b974-42d93c1acf31 Poland 363cf6ca-f302-42dd-a5ed-47be4e9db020 Poland 3fb84022-cf83-4ff7-8570-ff78e849b002 Norway a42fe505-8332-4882-89b3-219c9e139e96 Netherlands 36cbfde9-9e75-44a2-af0f-88d6f851e714 Estonia 7e11b1c7-8318-4ed4-8517-5cda17eea558 Hungary 8abf08c8-49cd-426d-b8e5-6a15ebaf7834 Hungary 43dcc3c8-5b02-4676-beb3-6370648b6ee9 Finland d873af9a-ce14-4361-8c97-487a8f0528c6 France a6183616-8302-4a0b-b713-27bd3e8044d5 Poland 6f622098-3e6e-4775-bb65-74cf164e08d7 Germany d4123054-94eb-4095-9348-377b72fdd293 France 60a1ed29-63d4-4dc1-956f-77c310073b31 Germany
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

ABB EcoSolutions	Yes
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill
End Of Life Disassembling Instructions	1SBC101080M6801
Environmental Product Declaration - EPD	1SBD250584E3000
Improved Energy Efficiency for Customers	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 92.7 %

Certificates and Declarations

A2L Certificate – UL	9AKK108469A4875 9AKK108469A4879
ABS Certificate	ABS_20-2060694-PDA
BV Certificate	BV_2634H24898C0
CB Certificate	CB_SE-113345
CCC Certificate	CCC_2024010304656669
CQC Certificate	CQC2010010304445624 CQC2020010304298240
Declaration of Conformity - CCC	2020980304001253 2020980304001082
Declaration of Conformity - CE	1SBD250000U1000
Declaration of Conformity - UKCA	1SBD250031U1000
DNV Certificate	DNV_TAE00001AF-4
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
KC Certificate	KC_HW02016-15005C
LR Certificate	LRS_LR23403517TA-02
RINA Certificate	RINA_ELE142224XG
RMRS Certificate	RMRS_1802705280
UL Certificate	UL-US-2150887-5 UL-CA-2142658-5
UL Listing Card	E312527

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	87 mm
Package Level 1 Depth / Length	79 mm
Package Level 1 Height	47 mm
Package Level 1 Gross Weight	0.27 kg
Package Level 1 EAN	3471523110618
Package Level 2 Units	box 27 piece
Package Level 2 Width	250 mm
Package Level 2 Depth / Length	300 mm
Package Level 2 Height	315 mm
Package Level 2 Gross Weight	7.29 kg

External Classifications and Standards

Object Classification Code	Q
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
ETIM 9	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4758 >> lec Contactors
E-Number (Finland)	3705804
E-Number (Sweden)	3211343

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF16

