#### **Specification sheet**



EU Stage IIIA / EPA Tier 3 / TA Luft Compliant





#### **Description**

The QSB5 incorporates the latest diesel engine technology, including a high pressure common rail fuel system for greater fuel efficiency, lower noise and reduced emissions.

#### **Features**

**Full-Authority Electronic Controls** - Optimize engine operation and deliver critical information for controlling costs, reducing maintenance and seamless integration with other components.

**Holset HX35 Wastegated Turbo** - Wastegated design optimizes transient response.

Low-Maintenance Fuel Filter Assembly - The fuel filter incorporates an integral water separator and water-in-fuel sensor; 500-hour filter life with easy top-load replacement using standard Fleetguard® filters.

Coolpac Integrated Design - Products are supplied complete with cooling package and air cleaner kit for a complete power package. Each component has been specifically developed and rigorously tested for G-Drive products, ensuring high performance, durability and reliability.

**Service and Support** - G-Drive products are backed by an uncompromising level of technical support and after sales service, delivered through a world class service network.



This engine has been designed in facilities certified to ISO9001 and manufactured in facilities certified to ISO9001 or ISO9002.

# **1500 rpm (50 Hz ratings)**

Gross engine output			Net engine output		Typical generator set output						
Standby Prime Base		Standby	Prime	Base	Standby (ESP)		Prime (PRP)		Base (COP)		
kWm/BHP			kWm/BHP		kWe	kVA	kWe	kVA	kWe	kVA	
103/138	89/119	81/108	95/127	82/110	74/99	80	100	73	91	69	86

# **1800 rpm (60 Hz ratings)**

Gross engine output			Net engine output		Typical generator set output						
Standby Prime Base		Standby	Prime	Base	Standby (ESP)		Prime (PRP)		Base (COP)		
kWm/BHP			kWm/BHP		kWe	kVA	kWe	kVA	kWe	kVA	
119/160	104/139	95/127	107/144	93/125	54/113	90	113	82	103	78	98

# **General engine data**

Туре	4 cycle, in-line, 4 cylinder diesel		
Bore mm	107 mm (4.21 in.)		
Stroke mm	124 mm (4.88 in.)		
Displacement litre	4.5 litre (275 in. <sup>3</sup> )		
Cylinder block	Cast iron, 4 cylinder		
Battery charging alternator	100 amps		
Starting voltage	24 volt, negative ground		
Fuel system	Direct injection		
Fuel filter	Dual spin-on fuel filters with water separator		
Lube oil filter type(s)	Spin-on full flow filter		
Lube oil capacity (I)	12.2		
Flywheel dimensions	SAE3		
t @ 10	·		

<sup>\*\* @ 13</sup> mm H<sub>2</sub>0

## Fuel consumption 1500 (50 Hz)

%	% kWm		L/ph	g/kWh				
Standby Power								
100	94	126	25	6.7				
Prime Pow	Prime Power							
100	81	109	22	5.9				
75	61	82	18	4.7				
50	41	55	12	3.2				
25	20	27	6	1.7				
Continuou	Continuous Power							
100	74	99	21	5.6				

## Fuel consumption 1800 (60 Hz)

%	kWm	ВНР	L/ph	g/kWh			
Standby P	ower						
100	108	145	29	7.7			
Prime Power							
100	94	126	26	6.9			
75	70	95	21	5.6			
50	47	63	15	3.9			
25	23	32	8	2.2			
Continuou	s Power						
100	84	113	24	6.2			

# Weights and dimensions (Engine only)

Length	Width	Height	Weight (dry)
mm	mm	mm	kg
821	739	982	352

## **Ratings definitions**

Emergency Standby Power (ESP):	Limited-Time Running Power (LTP):	Prime Power (PRP):	Base Load (Continuous) Power (COP):
Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power to a constant electrical load for limited hours. Limited-Time Running Power (LTP) is in accordance with ISO 8528.	Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.	Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) in accordance with ISO 8528, ISO 3046, AS 2789, DIN6271 and BS 5514.

For more information contact your local Cummins distributor or visit power.cummins.com

