



DSA*

PNEUMATICALLY OPERATED DIRECTIONAL CONTROL VALVE

SUBPLATE MOUNTING


DSA3 ISO 4401-03 (CETOP 03)

DSA5 ISO 4401-05 (CETOP R05)


p max (see performances table)

Q nom (see performances table)


MOUNTING INTERFACE DSA3



MOUNTING INTERFACE DSA5




OPERATING PRINCIPLE





1 - IDENTIFICATION CODE



2 - PERFORMANCES (with mineral oil of viscosity 36 cSt at 50°C)

		DSA3	DSA5
Maximum working pressure:			
- P A B ports	bar	350	320
- T port without Y external drain (standard for DSA3)		25	25
- T port with Y external drain (only for DSA5)		-	320
Piloting pressure	bar	4	4,5
min		12	12
max			
Nominal flow	l/min	75	120
Ambient temperature range	°C	-20 / +50	
Fluid temperature range	°C	-20 / +80	
Fluid viscosity range	cSt	10 ÷ 400	
Recommended viscosity	cSt	25	
Fluid contamination degree		according to ISO 4406:1999 class 20/18/15	
Mass	kg		
single operation valve		1,3	3,2
double operation valve		1,7	4,0

3 - HYDRAULIC FLUIDS

Use mineral oil-based hydraulic fluids HL or HM type, according to ISO 6743-4. For these fluids, use NBR seals (code N).

For fluids HFDR type (phosphate esters) use FPM seals (code V).

For the use of other fluid types such as HFA, HFB, HFC, please consult our technical department.


Using fluids at temperatures higher than 80 °C causes a faster degradation of the fluid and of the seals characteristics.

The fluid must be preserved in its physical and chemical characteristics.




4 - SPOOL TYPE


Type S*:
2 operations - 3 positions
with spring centering




Type SA*:
1 operation side A
2 positions (central + external)
with spring centering




Type SB*:
1 operation side B
2 positions (central + external)
with spring centering




Type TA:
1 operation side A
2 external positions
with return spring



Type TB:
1 operation side B
2 external positions
with return spring



Type RK:
2 operations - 2 positions
with mechanical retention




Besides the diagrams shown, which are the most frequently used, other special versions are available: consult our technical department for their identification and operating limits.



5 - PRESSURE DROPS Δp -Q (values obtained with viscosity 36 cSt at 50 °C)

5.1 - Pressure drops Δp -Q DSA3



For pressure drops between A and B lines of spools S10, S20, S21, S22 and S23, which are used in the regenerative diagram, refer to curve 5.

PRESSURE DROPS WITH VALVE IN ENERGIZED POSITION


SPOOL TYPE	FLOW DIRECTION			
	P-A	P-B	A-T	B-T
	CURVES ON GRAPH			
S1, SA1, SB1	2	2	3	3
S2, SA2, SB2	1	1	3	3
S3, SA3, SB3	3	3	1	1
S4, SA4, SB4	6	6	6	6
S5	2	1	3	3
S6	2	2	3	1
S7, S8	6	6	6	6
S9	2	2	3	3
S10	1	3	1	3
S11	2	2	1	3
S12	2	2	3	3
S17	2	2	3	3
S18	1	2	3	3
S19	2	2	3	3
S20	1	5	2	
S21	5	1		2
S22	1	5	2	
S23	5	1		2
TA, TB	2	2	2	2
TA02, TB02	2	2	2	2
TA23, TB23	3	3		
RK	2	2	2	2
RK02	2	2	2	2
RK1, 1RK	2	2	2	2

PRESSURE DROPS WITH VALVE IN DE-ENERGIZED POSITION

SPOOL TYPE	FLOW DIRECTION				
	P-A	P-B	A-T	B-T	P-T
	CURVES ON GRAPH				
S2, SA2, SB2					2
S3, SA3, SB3			3	3	
S4, SA4, SB4					5
S5		4			
S6				3	
S7, S8					5
S10	3	3			
S11			3		
S18	4				
S22			3	3	
S23			3	3	




5.2 - Pressure drops Δp -Q DSA5



PRESSURE DROPS WITH VALVE IN ENERGIZED POSITION

SPOOL TYPE	FLOW DIRECTION			
	P-A	P-B	A-T	B-T
	CURVES ON GRAPH			
S1, SA1, SB1	2	2	1	1
S2, SA2, SB2	3	3	1	1
S3, SA3, SB3	3	3	2	2
S4, SA4, SB4	1	1	2	2
S5	2	1	1	1
S6, S11	3	3	2	2
S7, S8	1	1	2	2
S9	3	3	2	2
S10	1	1	1	1
S12	2	2	1	1
S17, S19	2	2	1	1
S18	1	2	1	1
S20, S21				
S22, S23				
TA, TB	3	3	2	2
TA02, TB 02	3	3	2	2
TA23, TB23	4	4		
RK	3	3	2	2
RK02	3	3	2	2
RK1, 1RK	3	3	2	2



PRESSURE DROPS WITH VALVE IN DE-ENERGIZED POSITION


SPOOL TYPE	FLOW DIRECTION				
	P-A	P-B	A-T	B-T	P-T
	CURVES ON GRAPH				
S2, SA2, SB2					5
S3, SA3, SB3			6	6	
S4, SA4, SB4					5
S5		3			
S6				6	
S7					5
S8					5
S10	3	3			
S11			6		
S18	3				
S22					
S23					



6 - OPERATING LIMITS

The curves define the flow rate operating fields according to the valve pressure of the different versions. The values have been obtained according to ISO 6403 norm, with mineral oil viscosity 36 cSt at 50 °C and filtration according to ISO 4406:1999 class 18/16/13.


6.1 - DSA3



SPOOL TYPE	CURVE	
	P-A	P-B
S1,SA1,SB1	1	1
S2, SA2, SB2	1	1
S3, SA3, SB3	2	2
S4, SA4, SB4	3	3
S5	1	1
S6	3	2
S7	3	3
S8	3	3
S9	1	1
S10	1	1
S11	2	3
S12	1	1

SPOOL TYPE	CURVE	
	P-A	P-B
S17	1	1
S18	1	1
S19	1	1
S20	4	4
S21	4	4
S22	5	4
S23	4	5
TA, TB	1	1
TA02, TB02	1	1
TA23, TB23	1	1
RK	1	1
RK02	1	1
RK1, 1RK	1	1

6.2 - DSA5



SPOOL TYPE	CURVE	
	P-A	P-B
S1,SA1,SB1	1	1
S2, SA2, SB2	1	1
S3, SA3, SB3	3 *	3 *
S4, SA4, SB4	4	4
S5		
S6		
S7		
S8		
S9		
S10		
S11		
S12		

SPOOL TYPE	CURVE	
	P-A	P-B
S17		
S18		
S19		
S20		
S21		
S22		
S23		
TA, TB	2 *	2 *
TA02, TB02		
TA23, TB23		
RK		
RK02		
RK1, 1RK		


* **NOTE:** for spools S3 and TA, the curve has been obtained with a min. piloting pressure of 4,5 bar. If the minimum piloting pressure used is 5,5 bar, refer to the curve n° 1 (320 bar - 120 l/min).

NOTE: The values indicated in the graphs are relevant to the standard valve. The operating limits can be considerably reduced if a 4-way valve is used with port A or B plugged.




7 - INSTALLATION

Configurations with centering and return springs can be mounted in any position; type RK valves - without springs and with mechanical detent - must be mounted with the longitudinal axis horizontal. Valve fixing is by means of screws or tie rods, with the valve mounted on a lapped surface, with values of planarity and smoothness that are equal to or better than those indicated in the drawing. If the minimum values of planarity and/or smoothness are not met, fluid leakage between valve and mounting surface can easily occur.




8 - OVERALL AND MOUNTING DIMENSIONS DSA3

DSA3 - S*
DSA3 - RK



DSA3 - TA
DSA3 - SA*
DSA3 - TA23



dimensions in mm

1	Mounting surface with sealing rings
2	1/4" BSP connection for pneumatic operation
3	Hexagon: spanner 36 Tightening torque 35 - 40 Nm



Valve fastening	4 bolts TCEI M5x30 (recommended class 12.9)
Tightening torque:	5 Nm (bolts A 8.8) 8 Nm (bolts A 12.9)
Threads of mounting holes:	M5x10
Sealing rings:	4 OR type 2037 (9.25x1.78) - 90 Shore

operation position configuration SB*, TB and TB23





9 - OVERALL AND MOUNTING DIMENSIONS DSA5

DSA5 - S*
DSA5 - RK



DSA5 - TA
DSA5 - SA*
DSA5 - TA23



operation position configuration SB*, TB and TB23

dimensions in mm

1	Mounting surface with sealing rings
2	1/4" BSP connection for pneumatic operation
3	Hexagon: spanner 41 Tightening torque 55 - 60 Nm

Valve fastening:	4 screws TCEI M6x40 (recommended class 12.9)
Tightening torque:	8 Nm (bolts A 8.8) - 14 Nm (bolts A 12.9)
Threads of mounting holes:	M6x10
Sealing rings:	5 OR type 2050 (12.42x1.78) - 90 Shore 1 OR type 2037 (9.25x1.78) - 90 Shore

10 - SUBPLATES (See catalogue 51 000)	DSA3	DSA5
Type with rear ports	PMMD-AI3G	PMD4-AI4G
Type with side ports	PMMD-AL3G	PMD4-AL4G
Threading of ports P, T, A, B,	3/8" BSP	1/2" BSP



DIPLOMATIC OLEODINAMICA SpA
20025 LEGNANO (MI) - P.le Bozzi, 1 / Via Edison
Tel. 0331/472111 - Fax 0331/548328