

FP-100S



FAMCO
هایپر صنعت

■ FP-100S

Product Code: 10140

Product Description: FirePro

Fire Extinguishing Generator FP-100S.

Features:

- UL, KIWA, BSI, ActivFire Approved

TECHNICAL INFORMATION

Model	FP-100S
Activation mechanism	Thermal Electrical (min 1.5V DC, 0.8A in 3-4 sec)
Activator type	Heating element with 2.3 ohm resistance
Current intensity to be tested	Maximum 5 mA
Weight (gross)	1370 g (excluding bracket)
Mass of FPC compound	100 g
Operational discharge time	5 - 10 seconds
Discharge length	1 m
Dimensions (Height : Diameter)	155 mm : 84 mm (incl. connector housing)
Fire class	A, B, C, F

Operating temperatures: -54°C to +54°C | Generators are provided complete with brackets



www.famcocorp.com
E-mail: info@famcocorp.com
@famco_group

Tel: +91-48000049
Fax: +91-44994642

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)
روبروی پالایشگاه نفت پارس، پلاک ۱۲

FP-200S



www.famcocorp.com

E-mail: info@famcocorp.com

@famco_group

Tel: +91-44-2666666

Fax: +91-44-2666666

FAMCO

هایپر صنعت

■ FP-200S

Product Code: 10142

Product Description: FirePro

Fire Extinguishing Generator FP-200S.

Features:

- UL, KIWA, BSI, ActivFire Approved

TECHNICAL INFORMATION

Model	FP-200S
Activation mechanism	Thermal Electrical (min 1.5V DC, 0.8A in 3-4 sec)
Activator type	Heating element with 2.3 ohm resistance
Current intensity to be tested	Maximum 5 mA
Weight (gross)	1840 g (excluding bracket)
Mass of FPC compound	200 g
Operational discharge time	5 - 10 seconds
Discharge length	2 m
Dimensions (Height : Diameter)	185 mm : 84 mm (incl. connector housing)
Fire class	A, B, C, F

Operating temperatures: -54°C to +54°C | Generators are provided complete with brackets

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

روبروی پالایشگاه نفت پارس، پلاک ۱۲

FP-500S



FAMCO
هایپر صنعت

■ FP-500S

Product Code: 10145

Product Description: FirePro

Fire Extinguishing Generator FP-500S.

Features:

- UL, KIWA, BSI, ActivFire Approved

TECHNICAL INFORMATION

Model	FP-500S
Activation mechanism	Thermal Electrical (min 1.5V DC, 0.8A in 3-4 sec)
Activator type	Heating element with 2.3 ohm resistance
Current intensity to be tested	Maximum 5 mA
Weight (gross)	3340 g (excluding bracket)
Mass of FPC compound	500 g
Operational discharge time	5 - 10 seconds
Discharge length	3 m
Dimensions (Height : Diameter)	295 mm : 84 mm (incl. connector housing)
Fire class	A, B, C, F

Operating temperatures: -54°C to +54°C | Generators are provided complete with brackets

www.famcocorp.com

E-mail: info@famcocorp.com

@famco_group

Tel: ۰۲۱-۴۸۰۰۰۰۰۴۹

Fax: ۰۲۱-۴۴۹۹۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

روبروی پالایشگاه نفت پارس، پلاک ۱۲