

FP-20



■ FP-20SE

Product Code: 10135

Product Description: FirePro Fire Extinguishing Generator FP-20SE.

Features:

- UL, KIWA, BSI, ActivFire Approved
- This model discharges through two sets of outlets (top & bottom)

■ FP-20TH

Product Code: 10649

Product Description: FirePro Fire Extinguishing Generator FP-20TH.

Features:

- This model can be activated by a Bulb Thermal Actuator only and discharges through one outlet only (bottom).

■ FP-20T

Product Code: 10620

Product Description: FirePro Fire Extinguishing Generator FP-20T.

Features:

- KIWA Approved
- Under Process to be UL, BSI, ActivFire Approved
- This model discharges through one outlet only (bottom).

TECHNICAL INFORMATION

Model	FP-20SE / FP-20T / FP-20TH*
Activation mechanism	Electrical (min. 1.5V DC, 0.8A in 3-4 sec) *FP-20TH Thermal Activation Only
Current intensity to be tested	Maximum 5 mA
Weight (gross)	310 g (excluding bracket)
Mass of FPC compound	20 g
Operational discharge time	5 - 10 seconds
Discharge length	1 m
Dimensions (Height : Diameter)	170 mm : 32 mm (incl. connector housing)
Fire Class	A, B, C, F

Operating temperatures: -54°C to +54°C | Generators are provided complete with brackets



www.famcocorp.com

E-mail: info@famcocorp.com

@famco_group

Tel: +91-48000049

Fax: +91-48994642

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

روبروی پالایشگاه نفت پارس، پلاک ۱۳

FP-40



FAMCO هایپر صنعت

■ FP-40S

Product Code: 10136

Product Description: FirePro Fire Extinguishing Generator FP-40S.

Features:

- UL, KIWA, BSI, ActivFire Approved
- This model discharges through two sets of outlets (top & bottom)

■ FP-40T

Product Code: 10609

Product Description: FirePro Fire Extinguishing Generator FP-40T.

Features:

- KIWA Approved
- Under Process to be UL, BSI, ActivFire Approved
- This model discharges through one outlet only (bottom).

TECHNICAL INFORMATION

Model	FP-40S / FP-40T
Activation mechanism	Thermal Electrical (min 1.5V DC, 0.8A in 3-4 sec)
Activator type	Heating element with 2.3 ohm resistance
Current intensity to be tested	Maximum 5 mA
Weight (gross)	610 g (excluding bracket)
Mass of FPC compound	40 g
Operational discharge time	5 - 10 seconds
Discharge length	1 m
Dimensions (Height : Diameter)	145 mm : 51 mm (incl. connector housing)
Fire class	A, B, C, F

Operating temperatures: -54°C to +54°C | Generators are provided complete with brackets



www.famcocorp.com

E-mail: info@famcocorp.com

@famco_group

Tel: ۰۲۱-۴۸۰۰۰۰۴۹

Fax: ۰۲۱-۴۴۹۹۴۶۴۲

تهران، کیلومتر ۲ بزرگراه لشگری (جاده مخصوص کرج)

روبروی پالایشگاه نفت پارس، پلاک ۱۲

FP-80



■ FP-80S

Product Code: 10138

Product Description: FirePro Fire Extinguishing Generator FP-80S.

Features:

- UL, KIWA, and BSI Approved
- This model discharges through two sets of outlets (top & bottom)

■ FP-80T

Product Code: 10617

Product Description: FirePro Fire Extinguishing Generator FP-80T.

Features:

- UL, KIWA, and BSI Approved
- This model discharges through one outlet only (bottom).

TECHNICAL INFORMATION

Model	FP-80S / FP-80T
Activation mechanism	Thermal Electrical (min 1.5V DC, 0.8A in 3-4 sec)
Activator type	Heating element with 2.3 ohm resistance
Current intensity to be tested	Maximum 5 mA
Weight (gross)	870 g (excluding bracket)
Mass of FPC compound	80 g
Operational discharge time	5 - 10 seconds
Discharge length	2 m
Dimensions (Height : Diameter)	185 mm x 51 mm (incl. connector housing)
Fire class	A, B, C, F

Operating temperatures: -54°C to +54°C | Generators are provided complete with brackets



www.famcocorp.com

E-mail: info@famcocorp.com

@famco_group

Tel: ۰۲۱-۴۸۰۰۰۰۴۹

Fax: ۰۲۱-۴۴۹۹۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

روبروی پالایشگاه نفت پارس، پلاک ۱۲