

Power Cable 3 x 25 (N)YY-O Flexible (0.6/1KV)

P.V.C - insulated & Sheathed, Multi-Core Cable with Flexible Conductor Type NYY-F, 0.6/1 KV ACC(INSO 3569-1)

Cable Layer Construction	CU , PVC , PVC , PVC			LV	
Applicable Standard(s)	IEC 60502-1 & INSO 3569-1 & IEC 60228 & DIN VDE 0271				
Description		Unit	Specification		
CONDUCTOR	CU	Material	****	Plain Annealed Copper	
		TYPE	****	Flexible (Class 5) RF	
		No.of core & Conductor Area	L	no (mm ²)	2 x 25
			N		1 x 25
			PE		0
		No & Dia of Wire	L	no (mm)	189 x 0.39
N	189 x 0.39				
PE	0				
Shape	****	ROUND			
INSULATION	PVC	Material	****	Extruded PVC	
		Thickness	L	1.2	
			N	1.2	
			PE	0.0	
Colour	L:Black,Brown ,N:Blue				
Filler	PVC	Material	****	Extruded PVC	
		Thickness	mm	1.0	
Outer Sheath	PVC	Material	****	Extruded PVC	
		Thickness	mm	1.8	
		Colour	****	Black	
Overall diameter (Approx.)		mm	25.4		
Cable Weight (Approx.)		Kg / km	1,289		
Packing		****	Drum		
Rated Voltage U ₀ /U (Um)		KV	0.6 / 1 (1.2)		
System Frequency		Hz	50		
DC conductor resistant At 20 °C		Ω/ Km	0.78		
Conductor Short Circuit Current (1 Sec)		KA	2.78		
Test voltage		KV	4		
Max.Short circuit withstand current temperature		°C	+ 160		
OPeration temperature		°C	- 30 to +70		
Special Proerties		Flame Retardant	IEC 60332-1-2		

(افشار تراد) KHORASAN ELECTRIC IND.CO INSO3569-1 6932568916 0.6 /1KV NYY-O 3x25 mm2 RF FLEXIBLE MADE IN IRAN CE

CU Copper	PET Polyester Tape	CWC+CT Concentric Copper Wire Conductor+Copper Tape
TiCu Tinned Copper	Al-PET Aluminum Polyester Tape	CWS+CT Concentric Copper Wire Screen+Copper Tape
MGT Mica Glass Tape	CU-PET Copper Polyester Tape	SWA Steel Wire Armour
PVC Polyvinyl Chloride	TDW Tinned Drain Wire	SWB Steel Wire Braid
PE Polyethylene	CWB Copper Wire Braid	DTA Double Tape Armour
XLPE Cross Linked Polyethylene	TCWB Tinned Copper Wire Braid	LSPVC Low Smoke PVC
SR Silicone Rubber	OSCR Overall Screen	LSFOH Low Smoke Free Of Halogen

Shafiei