





LIFECO-227 SUPPRESSION SYSTEM




E-mail: info@famcocorp.com

@famco_group





LIFECO227ea Suppression System




Hepta Flouroprane is liquefied compressed Colorless, Odorless, Electrically non-conductive gas, works to quench fires in seconds & hold damage to a max.

Suppresses Fire primarily by physically cooling flame through removing heat energy, & interrupting the combustion reaction to an extent that cannot sustain itself.


Waterless Fire Suppressant Does not Leave residues, Particulate, Water or Corrosion.


- · LIFECO 227 is an Engineered & Pre-Engineered Computer Design to protect Specific Hazards.
- $\cdot \ \text{With LIFECO 227 Clean agent system you assured fast, efficient, environmentally safe fire \ Extinguishment.}$
- · Inert on people & safe on Environment
- · Active on fire with complete Extinguishment capability designed to fully discharge with in seconds.
- $\cdot \ \, \text{Three dimensional suppression, \& with effective } \ \, \text{penetration to knock down fires in hidden spaces.}$
- · Zero Ozone depletion Potential.
- · Superior to Water & Dry chemicals.
- · Suitable for class A, B, C fires.





@famco_group







LIFECO227ea Suppression System




LIFECO-227 System provide safe fire protection for life & assets by utilizing UL/FM Certified" HFC227 ea" Clean agent gas.

ECONOMICAL EFFECTIVE

LIFECO-227 System utilizes the Non-Ozone depleting clean agent "HFC-227ea" that protects the earth Ozone layer.



UNCOMPLICATED



ODORLESS

NFPA 2001standard rates "HFC-227ea" as an effective substitute for Halon g1301.Hence safe on global scale.

TOTAL FLOODING NO DAMAGE

In accordance with U.S.EPA,(SNAP) state that "HFC-227 ea" is an efficient, non ozone depleting Halon 1301 replacement in the use of Total Flooding System.

SELF CONTAINED

For use in occupied & unoccupied spaces.

Features

CF3 CHFCF3-Hepta Fluoropropane is liquified compressed colorless, odorless, electrically, non-conductive gas, works to quench fires in seconds & hold damage to a max.

Suppresses fire primarily by physically cooling flame through removing heat energy & Interrupting the combustion reaction to an extent that cannot sustain itself. Waterless fire suppressant does not leave residues, particulates, Water or corrosion.

** 360 PSI and 500 PSI

- · Lower design concentration, Safe & Non-Toxic.
- · Active on fire with complete extinguishment capability designed to fully discharged within seconds.
- · Three Dimensional suppression & with effective penetration to knock down fires in hidden spaces.
- · Ability to recover quickly from business disruption.
- · No cost of down time.
- · Zero Ozone depletion potential.
- · Superior to water & dry chemicals.
- · Suitable for Class A, B, C fires.
- · LIFECO-227 is an Engineered & Pre-Engineered computer designed to protect specific Hazards.
- · With LIFECO-227 Clean agent system you assured of fast, efficien & environmentally safe fire Extinguishment.
- · Recognized and certified by the top independent listing & approval parties NFPA,UL,FM,U.S.EPA...

Application



OIL REFINERIES

LABS





AIRPORTS



SERVER ROOM



🙈 w w w . fa m c o c o r p . c o m

🔁 E-mail: info@famcocorp.com

@famco_group

Теl:۰۲۱– ۴ Л о о о о Р 9 Fax:∘۲۱ – ۴۴99۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

روبـروی یالایشگاه نفت یـارس، یلاک ۱۲




LIFECO227ea Suppression System

Engineered Cylinder Filling Data

500 PSI		
Part No	Weight of the Agent (lbs.)	Valve Size
LF90020-EH, LF 90020-EH-SS	9-19	1" Valve
LF90035-EH, LF 90035-EH-SS	16-33	1" Valve
LF90070-EH, LF 90070-EH-SS	31-67	1" Valve
LF 90100-FH, LF 90100-FH-SS	44-94	1" Valve
LF90100-EH, LF90100-EH-SS	44-94	1½" Valve
LF90150-EH, LF 90150-EH-SS	66-143	1 ½" Valve
LF90250-EH, LF 90250-EH-SS	109-237	1½" Valve
LF90375-EH, LF 90375-EH-SS	163-356	2 ½" Valve
LF90560-EH, LF 90560-EH-SS	241-527	2 ½" Valve
LF 90650-EH, LF 90650-EH-SS	285-624	2 ½" Valve
LF 90650-FH	285-624	3" Valve
LF 90800-FH	360-788	3" Valve
LF 90800-EH	360-788	4" Valve
LF 91000-FH	445-974	3" Valve
LF 91000-EH	445-974	4" Valve
LF91200-EH	519-1137	4" Valve

360 PSI		
Part No	Weight of the Agent (lbs.)	Valve Size
LF90020-E, LF 90020-E-SS	9-20	1" Valve
LF90035-E, LF 90035-E-SS	16-35	1" Valve
LF90070-E, LF 90070-E-SS	31-71	1" Valve
LF90100-F, LF 90100-F-SS	44-101	1" Valve
LF90100-E, LF 90100-E-SS	44-101	1 ½" Valve
LF90150-E, LF 90150-E-SS	66-152	1 ½" Valve
LF90250-E, LF 90250-E-SS	109-253	1 ½" Valve
LF90375-E, LF 90375-E-SS	163-379	2½" Valve
LF90560-E, LF 90560-E-SS	241-561	2 ½" Valve
LF90800-E	353-806	4" Valve
LF91000-E	439-1008	4" Valve
LF91200-E	519-1200	4" Valve

Structure



- ⊗ w w w . f a m c o c o r p . c o m
- E-mail: info@famcocorp.com
- @famco_group

- Tel:∘۲۱– κ Λ ∘ ∘ ∘ ∘ κ ۹
- Fax:∘۲1 ۴۴99۴۶۴۲



- (a) www.famcocorp.com
- E-mail: info@famcocorp.com
- @famco_group

- Tel:•۲1- ۴ Λ • • ۴ ٩
- Fax:011 ۴۴99۴۶۴۲