



Main

| | |
|-------------------------------------|---|
| Range | Acti 9 |
| Product name | Acti 9 iDPN N Vigi |
| Product or component type | Residual current breaker with overcurrent protection (RCBO) |
| Device short name | IDPN N Vigi |
| Device application | Distribution |
| Poles description | 1P + N |
| Neutral position | Left |
| Network type | AC |
| Trip unit technology | Thermal-magnetic |
| Curve code | C |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type AC |
| Electrical symbol | 6000 A Icn at 220...240 V AC 50 Hz conforming to EN/IEC 61009-2-1 |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2 |

Complementary

| | |
|--------------------------------------|---|
| Device location in system | Outgoer |
| Network frequency | 50 Hz |
| Network frequency | 6000 A 100 % x Icn at 220...240 V AC 50 Hz conforming to EN/IEC 61009-2-1 |
| [Ue] rated operational voltage | 220...240 V AC 50 Hz |
| Magnetic tripping limit | 5...10 x In |
| Residual current tripping technology | Voltage independent |
| Network type | 400 V AC 50 Hz |
| Electrical symbol | Idm 6000 A at 220...240 V AC 50 Hz conforming to EN/IEC 61009-2-1 |
| Limitation class | 3 conforming to EN/IEC 61009-2-1 |
| Contact position indicator | Yes |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|--|---|
| Control type | Toggle |
| Local signalling | ON, OFF, fault trip |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Comb busbar and distribution block compatibility | Top or bottom: YES |
| Colour | White |
| Locking options description | Padlocking device |
| Connections - terminals | Single terminal top or bottom 1...16 mm ² rigid Single terminal top or bottom 1...10 mm ² flexible Single terminal top or bottom 1...10 mm ² flexible with ferrule |
| Location of connection | 15 mm for top or bottom connection |
| Location of connection | 2 N.m top or bottom |
| Earth-leakage protection | Integrated |

Environment

| | |
|-------------------------------|--|
| Standards | EN/IEC 61009-2-1 |
| Product certifications | VDE GOST |
| IP degree of protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution degree | 3 |
| Overtoltage category | III conforming to IEC 60364 |
| Electromagnetic compatibility | 8/20 µs impulse withstand, 250 A conforming to EN/IEC 61009-2-1 |
| Tropicalisation | 2 conforming to IEC 60068-1 |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 224 g |
| Package 1 Height | 4 cm |
| Package 1 width | 8.5 cm |
| Package 1 Length | 10 cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 6 |
| Package 2 Weight | 1.414 kg |
| Package 2 Height | 9.1 cm |
| Package 2 width | 10.7 cm |
| Package 2 Length | 25.4 cm |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 54 |
| Package 3 Weight | 13.213 kg |
| Package 3 Height | 30 cm |
| Package 3 width | 30 cm |
| Package 3 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| RECh Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |

Product out of China RoHS scope. Substance declaration for your information

| | |
|--------------------------|---|
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

A9D31640 is replaced by:



Residual Current Breaker with Overcurrent protection (RCBO) A9DE3640

residual current breaker with overcurrent protection (RCBO), Acti9 iCV40, 1P+N, 40 A, C Curve, 6000 A, 30 mA, AC type

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2020