

SIEMENS

Data sheet

3RT2023-1BB40



power contactor, AC-3e/AC-3, 9 A, 4 kW / 400 V, 3-pole, 24 V DC, auxiliary contacts: 1 NO + 1 NC, screw terminal, size: S0

product brand name	SIRIUS
product designation	Power contactor
product type designation	3RT2
General technical data	
size of contactor	S0
product extension	
• function module for communication	No
• auxiliary switch	Yes
power loss [W] for rated value of the current	
• at AC in hot operating state	0.6 W
• at AC in hot operating state per pole	0.2 W
• without load current share typical	5.9 W
type of calculation of power loss depending on pole	quadratic
insulation voltage	
• of main circuit with degree of pollution 3 rated value	690 V
• of auxiliary circuit with degree of pollution 3 rated value	690 V
surge voltage resistance	
• of main circuit rated value	6 kV
• of auxiliary circuit rated value	6 kV
maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1	400 V
shock resistance at rectangular impulse	
• at DC	10g / 5 ms, 7,5g / 10 ms
shock resistance with sine pulse	
• at DC	15g / 5 ms, 10g / 10 ms
mechanical service life (operating cycles)	
• of contactor typical	10 000 000
• of the contactor with added electronically optimized auxiliary switch block typical	5 000 000
• of the contactor with added auxiliary switch block typical	10 000 000
reference code according to IEC 81346-2	Q
Substance Prohibittance (Date)	10/01/2009
Weight	0.596 kg
Ambient conditions	
installation altitude at height above sea level maximum	2 000 m
ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-55 ... +80 °C
relative humidity minimum	10 %
relative humidity at 55 °C according to IEC 60068-2-30 maximum	95 %

Environmental footprint	
Environmental Product Declaration(EPD)	Yes
Global Warming Potential [CO2 eq] total	221 kg
Global Warming Potential [CO2 eq] during manufacturing	2.65 kg
Global Warming Potential [CO2 eq] during operation	219 kg
Global Warming Potential [CO2 eq] after end of life	-0.639 kg
Main circuit	
number of poles for main current circuit	3
number of NO contacts for main contacts	3
operating voltage	
• at AC-3 rated value maximum	690 V
• at AC-3e rated value maximum	690 V
operational current	
• at AC-1 at 400 V at ambient temperature 40 °C rated value	40 A
• at AC-1	
— up to 690 V at ambient temperature 40 °C rated value	40 A
— up to 690 V at ambient temperature 60 °C rated value	35 A
• at AC-3	
— at 400 V rated value	9 A
— at 500 V rated value	9 A
— at 690 V rated value	9 A
• at AC-3e	
— at 400 V rated value	9 A
— at 500 V rated value	9 A
— at 690 V rated value	9 A
• at AC-4 at 400 V rated value	8.5 A
• at AC-5a up to 690 V rated value	35.2 A
• at AC-5b up to 400 V rated value	7.4 A
• at AC-6a	
— up to 230 V for current peak value n=20 rated value	11.4 A
— up to 400 V for current peak value n=20 rated value	11.4 A
— up to 500 V for current peak value n=20 rated value	9.1 A
— up to 690 V for current peak value n=20 rated value	9 A
• at AC-6a	
— up to 230 V for current peak value n=30 rated value	7.6 A
— up to 400 V for current peak value n=30 rated value	7.6 A
— up to 500 V for current peak value n=30 rated value	6.1 A
— up to 690 V for current peak value n=30 rated value	6.1 A
minimum cross-section in main circuit at maximum AC-1 rated value	10 mm²
operational current for approx. 200000 operating cycles at AC-4	
• at 400 V rated value	4.1 A
• at 690 V rated value	3.3 A
operational current	
• at 1 current path at DC-1	
— at 24 V rated value	35 A
— at 60 V rated value	20 A
— at 110 V rated value	4.5 A
— at 220 V rated value	1 A
— at 440 V rated value	0.4 A
— at 600 V rated value	0.25 A
• with 2 current paths in series at DC-1	
— at 24 V rated value	35 A
— at 60 V rated value	35 A
— at 110 V rated value	35 A
— at 220 V rated value	5 A
— at 440 V rated value	1 A
— at 600 V rated value	0.8 A

<div><div>● with 3 current paths in series at DC-1</div><div><div>— at 24 V rated value</div><div>— at 60 V rated value</div><div>— at 110 V rated value</div><div>— at 220 V rated value</div><div>— at 440 V rated value</div><div>— at 600 V rated value</div></div><div>● at 1 current path at DC-3 at DC-5</div><div><div>— at 24 V rated value</div><div>— at 60 V rated value</div><div>— at 110 V rated value</div><div>— at 220 V rated value</div><div>— at 440 V rated value</div><div>— at 600 V rated value</div></div><div>● with 2 current paths in series at DC-3 at DC-5</div><div><div>— at 24 V rated value</div><div>— at 60 V rated value</div><div>— at 110 V rated value</div><div>— at 220 V rated value</div><div>— at 440 V rated value</div><div>— at 600 V rated value</div></div><div>● with 3 current paths in series at DC-3 at DC-5</div><div><div>— at 24 V rated value</div><div>— at 60 V rated value</div><div>— at 110 V rated value</div><div>— at 220 V rated value</div><div>— at 440 V rated value</div><div>— at 600 V rated value</div></div></div>	<div>35 A</div> <div>35 A</div> <div>35 A</div> <div>35 A</div> <div>2.9 A</div> <div>1.4 A</div> <div>20 A</div> <div>5 A</div> <div>2.5 A</div> <div>1 A</div> <div>0.09 A</div> <div>0.06 A</div> <div>35 A</div> <div>35 A</div> <div>15 A</div> <div>3 A</div> <div>0.27 A</div> <div>0.16 A</div> <div>35 A</div> <div>35 A</div> <div>35 A</div> <div>10 A</div> <div>0.6 A</div> <div>0.6 A</div>
<div><div>operating power</div><div>● at AC-3</div><div><div>— at 230 V rated value</div><div>— at 400 V rated value</div><div>— at 500 V rated value</div><div>— at 690 V rated value</div></div><div>● at AC-3e</div><div><div>— at 230 V rated value</div><div>— at 400 V rated value</div><div>— at 500 V rated value</div><div>— at 690 V rated value</div></div></div>	<div>2.2 kW</div> <div>4 kW</div> <div>4 kW</div> <div>7.5 kW</div> <div>2.2 kW</div> <div>4 kW</div> <div>4 kW</div> <div>7.5 kW</div>
<div><div>operating power for approx. 200000 operating cycles at AC-4</div><div>● at 400 V rated value</div><div>● at 690 V rated value</div></div>	<div>2 kW</div> <div>2.5 kW</div>
<div><div>operating apparent power at AC-6a</div><div>● up to 230 V for current peak value n=20 rated value</div><div>● up to 400 V for current peak value n=20 rated value</div><div>● up to 500 V for current peak value n=20 rated value</div><div>● up to 690 V for current peak value n=20 rated value</div></div>	<div>4.5 kVA</div> <div>7.8 kVA</div> <div>7.8 kVA</div> <div>10.7 kVA</div>
<div><div>operating apparent power at AC-6a</div><div>● up to 230 V for current peak value n=30 rated value</div><div>● up to 400 V for current peak value n=30 rated value</div><div>● up to 500 V for current peak value n=30 rated value</div><div>● up to 690 V for current peak value n=30 rated value</div></div>	<div>3 kVA</div> <div>5.2 kVA</div> <div>5.2 kVA</div> <div>7.2 kVA</div>
<div><div>short-time withstand current in cold operating state up to 40 °C</div><div>● limited to 1 s switching at zero current maximum</div><div>● limited to 5 s switching at zero current maximum</div><div>● limited to 10 s switching at zero current maximum</div><div>● limited to 30 s switching at zero current maximum</div><div>● limited to 60 s switching at zero current maximum</div></div>	<div>170 A; Use minimum cross-section acc. to AC-1 rated value</div> <div>170 A; Use minimum cross-section acc. to AC-1 rated value</div> <div>140 A; Use minimum cross-section acc. to AC-1 rated value</div> <div>104 A; Use minimum cross-section acc. to AC-1 rated value</div> <div>88 A; Use minimum cross-section acc. to AC-1 rated value</div>
<div>no-load switching frequency</div>	

• at DC	1 500 1/h
operating frequency	
• at AC-1 maximum	1 000 1/h
• at AC-2 maximum	1 000 1/h
• at AC-3 maximum	1 000 1/h
• at AC-3e maximum	1 000 1/h
• at AC-4 maximum	300 1/h
Control circuit/ Control	
type of voltage of the control supply voltage	DC
control supply voltage at DC rated value	24 V
operating range factor control supply voltage rated value of magnet coil at DC	
• initial value	0.8
• full-scale value	1.1
closing power of magnet coil at DC	5.9 W
holding power of magnet coil at DC	5.9 W
closing delay	
• at DC	50 ... 170 ms
opening delay	
• at DC	15 ... 18 ms
arcing time	10 ... 10 ms
control version of the switch operating mechanism	Standard A1 - A2
Auxiliary circuit	
number of NC contacts for auxiliary contacts instantaneous contact	1
number of NO contacts for auxiliary contacts instantaneous contact	1
operational current at AC-12 maximum	10 A
operational current at AC-15	
• at 230 V rated value	10 A
• at 400 V rated value	3 A
• at 500 V rated value	2 A
• at 690 V rated value	1 A
operational current at DC-12	
• at 24 V rated value	10 A
• at 48 V rated value	6 A
• at 60 V rated value	6 A
• at 110 V rated value	3 A
• at 125 V rated value	2 A
• at 220 V rated value	1 A
• at 600 V rated value	0.15 A
operational current at DC-13	
• at 24 V rated value	10 A
• at 48 V rated value	2 A
• at 60 V rated value	2 A
• at 110 V rated value	1 A
• at 125 V rated value	0.9 A
• at 220 V rated value	0.3 A
• at 600 V rated value	0.1 A
contact reliability of auxiliary contacts	1 faulty switching per 100 million (17 V, 1 mA)
UL/CSA ratings	
full-load current (FLA) for 3-phase AC motor	
• at 480 V rated value	7.6 A
• at 600 V rated value	9 A
yielded mechanical performance [hp]	
• for single-phase AC motor	
— at 110/120 V rated value	1 hp
— at 230 V rated value	1 hp
• for 3-phase AC motor	
— at 200/208 V rated value	2 hp
— at 220/230 V rated value	3 hp

— at 460/480 V rated value	5 hp
— at 575/600 V rated value	7.5 hp
contact rating of auxiliary contacts according to UL	A600 / P600
Short-circuit protection	
design of the fuse link <ul style="list-style-type: none">for short-circuit protection of the main circuit<ul style="list-style-type: none">with type of coordination 1 requiredwith type of assignment 2 requiredfor short-circuit protection of the auxiliary switch required	gG: 63A (690V,100kA), aM: 32A (690V,100kA), BS88: 63A (415V,80kA) gG: 25A (690V,100kA), aM: 20A (690V,100kA), BS88: 25A (415V,80kA) gG: 10 A (500 V, 1 kA)
Installation/ mounting/ dimensions	
mounting position	+/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface
fastening method	screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715
height	85 mm
width	45 mm
depth	107 mm
required spacing <ul style="list-style-type: none">with side-by-side mounting<ul style="list-style-type: none">forwardsupwardsdownwardsat the sidefor grounded parts<ul style="list-style-type: none">forwardsupwardsat the sidedownwardsfor live parts<ul style="list-style-type: none">forwardsupwardsdownwardsat the side	10 mm 10 mm 10 mm 0 mm 10 mm 10 mm 6 mm 10 mm 10 mm 10 mm 10 mm 6 mm
Connections/ Terminals	
type of electrical connection <ul style="list-style-type: none">for main current circuitfor auxiliary and control circuitat contactor for auxiliary contactsof magnet coil	screw-type terminals screw-type terminals Screw-type terminals Screw-type terminals
type of connectable conductor cross-sections <ul style="list-style-type: none">for main contacts<ul style="list-style-type: none">solidsolid or strandedfinely stranded with core end processingfor AWG cables for main contacts	2x (1 ... 2.5 mm²), 2x (2.5 ... 10 mm²) 2x (1 ... 2.5 mm²), 2x (2.5 ... 10 mm²) 2x (1 ... 2.5 mm²), 2x (2.5 ... 6 mm²), 1x 10 mm² 2x (16 ... 12), 2x (14 ... 8)
connectable conductor cross-section for main contacts <ul style="list-style-type: none">solidstrandedfinely stranded with core end processing	1 ... 10 mm² 1 ... 10 mm² 1 ... 10 mm²
connectable conductor cross-section for auxiliary contacts <ul style="list-style-type: none">solid or strandedfinely stranded with core end processing	0.5 ... 2.5 mm² 0.5 ... 2.5 mm²
type of connectable conductor cross-sections <ul style="list-style-type: none">for auxiliary contacts<ul style="list-style-type: none">solid or strandedfinely stranded with core end processingfor AWG cables for auxiliary contacts	2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²) 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²) 2x (20 ... 16), 2x (18 ... 14)
AWG number as coded connectable conductor cross section <ul style="list-style-type: none">for main contactsfor auxiliary contacts	16 ... 8 20 ... 14
Safety related data	

product function	
• mirror contact according to IEC 60947-4-1	Yes
• positively driven operation according to IEC 60947-5-1	No
• suitable for safety function	Yes
suitability for use safety-related switching OFF	Yes
service life maximum	20 a
test wear-related service life necessary	Yes
proportion of dangerous failures	
• with low demand rate according to SN 31920	40 %
• with high demand rate according to SN 31920	73 %
B10 value with high demand rate according to SN 31920	1 000 000
failure rate [FIT] with low demand rate according to SN 31920	100 FIT
ISO 13849	
device type according to ISO 13849-1	3
overdimensioning according to ISO 13849-2 necessary	Yes
IEC 61508	
safety device type according to IEC 61508-2	Type A
Electrical Safety	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front
Approvals Certificates	
General Product Approval	



Confirmation



KC

General Product Approval	EMV	Functional Safety	Test Certificates		Marine / Shipping
		Type Examination Certificate	Special Test Certificate	Type Test Certificates/Test Report	

Marine / Shipping			other		
				Miscellaneous	Confirmation

Railway	Dangerous goods	Environment			
Special Test Certificate	Transport Information			Environmental Confirmations	

Further information	
Information on the packaging	
https://support.industry.siemens.com/cs/ww/en/view/109813875	
Information- and Downloadcenter (Catalogs, Brochures,...)	
https://www.siemens.com/ic10	
Industry Mall (Online ordering system)	
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2023-1BB40	
Cax online generator	
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2023-1BB40	
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)	
https://support.industry.siemens.com/cs/ww/en/ps/3RT2023-1BB40	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)	


http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2023-1BB40&lang=en



Characteristic: Tripping characteristics, I_t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2023-1BB40/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2023-1BB40&objecttype=14&gridview=view1>





last modified:

7/19/2024