



accessories circuit breaker 3WL shunt trip AC 50/60Hz 208-240V/  
DC 220V 100% ed

Model	
Product brand name	SENTRON

General technical data	
Closing apparent power [VA]	15 V·A
Closing active power [W]	15 W
Power-on time electrically	100 ms

Voltage	
Surge voltage resistance	4 kV

Certificates					
Declaration of Conformity	Test Certificates	Shipping Approval	other		
 EG-Konf.	Miscellaneous	 RMRS	<a href="#">Environmental Confirmations</a>	<a href="#">Manufacturer Declaration</a>	Miscellaneous

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**  
[siemens.com/lowvoltage/catalogs](https://www.siemens.com/lowvoltage/catalogs)

**Industry Mall (Online ordering system)**  
[mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL9111-0AD06-0AA0](https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL9111-0AD06-0AA0)

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**  
[support.industry.siemens.com/cs/ww/en/ps/3WL9111-0AD06-0AA0](https://support.industry.siemens.com/cs/ww/en/ps/3WL9111-0AD06-0AA0)

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**  
[automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3WL9111-0AD06-0AA0](https://automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL9111-0AD06-0AA0)

**CAx-Online-Generator**  
[siemens.com/cax](https://www.siemens.com/cax)

**Tender specifications**  
[siemens.com/specifications](https://www.siemens.com/specifications)