

auxiliary current switch, 1 NO+1 NC for miniature circuit breaker 5SL, 5SY, 5SP Incorporated switch 5TL1, RCBO 5SU1, FI 5SV (for 5SU1 handle coupler 5ST3805-1 is required)



Model	
product brand name	SENTRON
product designation	Auxiliary current switch
design of the product	Mountable
electrical endurance (switching cycles) / typical	20 000
Voltage	
insulation voltage / rated value	440 V
surge voltage resistance / rated value	4 kV
Supply voltage	
operating frequency	50/60 Hz
protection class IP	IP20
Product details	
product component	
• auxiliary switch	Yes
number of fault signal contacts	0
number of NC contacts	1
number of NO contacts	1
number of CO contacts	0

product extension	auxiliary switch
-------------------	------------------

Connections

connectable conductor cross-section	
<ul style="list-style-type: none"> • minimum • maximum 	0.5 mm ² 2.5 mm ²
tightening torque / with screw-type terminals	
<ul style="list-style-type: none"> • maximum 	0.5 N·m
type of connectable conductor cross-sections / at AWG cables	24 ... 12

Mechanical Design

height	90 mm
width	9 mm
depth	70 mm
net weight	55 g

Environmental conditions

ambient temperature / during operation	
<ul style="list-style-type: none"> • minimum • maximum 	-25 °C 55 °C
ambient temperature / during storage	
<ul style="list-style-type: none"> • minimum permissible • maximum permissible 	-40 °C 75 °C

General Product Approval

Declaration of Conformity



CCC



UR



VDE

Miscellaneous



EG-Konf.

Test Certificates	Marine / Shipping	other	Railway
-------------------	-------------------	-------	---------

Miscellaneous



LRS



DNVGL.COM/AF

Miscellaneous

Vibration and Shock

Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

[siemens.com/lowvoltage/catalogs](https://www.siemens.com/lowvoltage/catalogs)

Industry Mall (Online ordering system)

mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3010

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

support.industry.siemens.com/cs/ww/en/ps/5ST3010





