

Miniature circuit breaker 400 V 6kA, 3-pole, C, 6A



Model	
product brand name	SENTRON
product designation	Miniature circuit breaker
design of the product	5SL miniature circuit breakers
General technical data	
number of poles	3
number of poles / note	3P
tripping characteristic class	C
mechanical service life (switching cycles) / typical	10 000
overvoltage category	III
degree of pollution	2
Voltage	
insulation voltage	440 V
<ul style="list-style-type: none"> <li>with multi-phase operation / at AC / rated value</li> </ul>	440 V
Supply voltage	
type of voltage	AC
operational current / at AC / rated value	6 A
supply voltage / at AC / rated value	400 V

operating voltage	
<ul style="list-style-type: none"> <li>• with multi-phase operation / at AC / maximum</li> <li>• at DC / rated value / maximum</li> </ul>	440 V 72 V
supply voltage frequency	
<ul style="list-style-type: none"> <li>• rated value</li> </ul>	50 Hz

### Protection class

protection class IP	IP20, with connected conductors
---------------------	---------------------------------

### Switching capacity

switching capacity current	
<ul style="list-style-type: none"> <li>• acc. to EN 60898 / rated value</li> <li>• acc. to IEC 60947-2 / rated value</li> </ul>	6 kA 6 kA
energy limitation class	3

### Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	0.7 W
suitability for operation	Residential buildings/infrastructure

### Product details

product function / neutral conductor switching	No
product feature / touch protection	Yes
product feature	
<ul style="list-style-type: none"> <li>• halogen-free</li> <li>• sealable</li> <li>• silicon-free</li> </ul>	Yes Yes Yes
product extension / installable / supplementary devices	Yes

### Connections

connectable conductor cross-section / solid	
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	0.75 mm <sup>2</sup> 25 mm <sup>2</sup>
connectable conductor cross-section / stranded	
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	0.75 mm <sup>2</sup> 25 mm <sup>2</sup>
connectable conductor cross-section / finely stranded / with core end processing	
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	0.75 mm <sup>2</sup> 25 mm <sup>2</sup>
tightening torque / with screw-type terminals	
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	2.5 N·m 3 N·m

### Mechanical Design

height	90 mm
width	54 mm
depth	76 mm
installation depth	70 mm
number of modular width units	3
mounting position	any
net weight	355 g

### Environmental conditions

influence of the surrounding temperature	Periodically +55°C, max. 95% humidity
ambient temperature	
• minimum	-25 °C
• maximum	45 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	75 °C

### Certificates

reference code	
• acc. to DIN EN 61346-2	F
• acc. to IEC 81346-2	F

### General Product Approval

### Declaration of Conformity



[TSE](#)



EG-Konf.

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

[siemens.com/lowvoltage/catalogs](https://www.siemens.com/lowvoltage/catalogs)

#### Industry Mall (Online ordering system)

[mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL6306-7](https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL6306-7)

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

[support.industry.siemens.com/cs/ww/en/ps/5SL6306-7](https://support.industry.siemens.com/cs/ww/en/ps/5SL6306-7)

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SL6306-7](https://automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SL6306-7)

#### CAX-Online-Generator

[siemens.com/cax](https://www.siemens.com/cax)

#### Tender specifications

[siemens.com/specifications](https://www.siemens.com/specifications)



