

WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY

**EDGER POWER
TROWEL
BT60H**



BETON TROWEL n.v.

tel. +32 (0)52 315 350

tel. +32 (0)52 315 351

fax +32 (0)52 303 739

info@betontrowel.com

www.betontrowel.com

Nijverheidsstraat 11

B-1840 Londerzeel - Belgium



- Two years warranty on gearbox
- Precision machined spider assembly
- Adjustable blade arms for fine tolerance
- Twin-tube folding handle for strength and operating cable protection



Specifications :

- Power options : Honda GX160 5.5hp, Robin EX17, electric 230V 1.5 kW
- Centrifugal clutch
- Dimensions length 1490 mm
 Height 910 mm
 Width 600 mm
- Working diameter : 600 mm
- Operating weight : 53 kg-63 kg (230V)
- Sound : 97-103 Lwa
 : 82-86 Lba
- Handle vibrations : 1.1 – 1.5 m/s
- Blade options :
 - Combination
 - Float pans

www.famcocorp.com

E-mail: info@famcocorp.com

@famco_group

Tel: ۰۲۱- ۴ ۸ ۰ ۰ ۰ ۰ ۴ ۹

Fax: ۰۲۱ - ۴ ۴ ۹ ۹ ۴ ۶ ۴ ۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

روبروی پالایشگاه نفت پارس، پلاک ۱۲

WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY

**POWER
TROWEL
BT75H**



BETON TROWEL n.v.

Tel. +32 (0)52 315 350

Tel. +32 (0)52 315 351

Fax +32 (0)52 315 359

info@betontrowel.com

www.betontrowel.com

Nijverheidsstraat 10

BE-1840 Londerzeel - Belgium



- Two year warranty on gearbox
- Precision machines spider assembly
- Adjustable blade arms for fine tolerance
- Tritube handle for strength and protection of operating cables
- Dual safety stops



Specifiactions :

- Power options : Honda GX160, BTP200
- Hoist hook
- Centrifugal clutch
- Dimensions length 1850 mm
 Height 960 mm
 Width 780 mm
- Working diameter : 75 cm
- Operating weight : 78 kg
- Sound : 97-103 Lwa
 : 82-86 Lba
- Handle vibrations : 1.1 – 1.5 m/s
- Blade options :
 - Finish: F75416B
 - Float pans: FP7754

WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY



BETON TROWEL n.v.

tel. +32 (0)52 315 350

tel. +32 (0)52 315 351

fax +32 (0)52 303 739

info@betontrowel.com

www.betontrowel.com

Nijverheidsstraat 11

B-1840 Londerzeel - Belgium

**POWER
TROWEL
BT90H**



- Two year warranty on gearbox
- Precision machines dpider assembly
- Adjustable blade arms for fine tolerance
- Tritube handle for strength and protection of operating cables
- Dual safety stops

Specifiactions :

- Power options : Honda GX160, Honda GX270, Robin EX17, electric 230V 2.2 kW
- Hoist hook
- Centrifugal clutch
- Dimensions length 1850 mm
 Height 960 mm
 Width 960 mm
- Working diameter : 90 cm
- Operating weight : 78 kg
- Sound : 97-103 Lwa
 : 82-86 Lba
- Handle vibrations : 1.1 – 1.5 m/s
- Blade options :
 - Finish
 - Combination
 - Float shoes
 - Float pans



WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY

**POWER TROWEL
DIESEL
BT90YDK**

BETON TROWEL n.v.

Tel. +32 (0)52 315 350

Tel. +32 (0)52 315 351

Fax +32 (0)52 315 359

info@betontrowel.com

www.betontrowel.com

Nijverheidsstraat 10

BE-1840 Londerzeel - Belgium



- Two year warranty on gearbox
- Precision machines spider assembly
- Adjustable blade arms for fine tolerance
- Tritube handle for strength and protection of operating cables
- Dual safety stops

Specifications :

- Brand/Model of drive unit: Yanmar L48N
- Make of engine: Japan
- Type of engine: Vertical cylinder, 4-cycle air-cooled
- Maximum Power: 3.5 kW
- Continuous Power: 3.1 kW
- Size of engine: 332x384x417mm
- Weight complete of engine: 35kg
- Noise level of engine: 92.50
- Start engine: Manual
- Fuel tank capacity: 2.4L
- Hoist hook
- Centrifugal clutch
- Dimensions trowel
 - Length 1850 mm
 - Height 960 mm
 - Width 960 mm
- Working diameter : 90 cm
- Operating weight : 78 kg



WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY

**POWER
TROWEL
BT120H**

BETON TROWEL n.v.

tel. +32 (0)52 315 350

tel. +32 (0)52 315 351

fax +32 (0)52 303 739

info@betontrowel.com

www.betontrowel.com

Nijverheidsstraat 11

B-1840 Londerzeel - Belgium



The perfect choice of the professional Finisher. A machine with an excellent balance of diameter, weight and power offering 2.5 times the performance of a 90cm machine.

- Tri tube laterally welded handle for strength and protection of control cables
- Dual stop safety system with electric deadman and centrifugal engine cut out.
- Chromed handle and guard ring for easy cleaning
- Precision machined spider assembly for maintaining machine balance and minimum parts wear
- Heavy duty gearbox with 24 month guarantee
- Lifting hook fitted as standard

Specifications :

- Power options : Honda GX270, Honda GX390, Robin 9HP
- Hoist hook
- Centrifugal clutch
- Dimensions length 2130 mm
 Height 1040 mm
 Width 1250 mm
- Working diameter : 120 cm
- Operating weight : 118 kg
- Sound : 97-103 Lwa
 : 82-86 Lba
- Handle vibrations : 1.1 – 1.5 m/s
- Blade options including Finish, Combination, Wide Finish, Float Shoes, Float pans, Plastic blades for light pigment finishes



WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY



BETON TROWEL n.v.

Tel. +32 (0)52 315 350

Tel. +32 (0)52 315 351

Fax +32 (0)52 315 359

info@betontrowel.com

www.betontrowel.com

Nijverheidsstraat 10

BE-1840 Londerzeel - Belgium

BTPT75H



BTPT75H PORTATROWEL

The PortaTrowel's lightweight design improves operator safety and allows for earlier commencement of concrete finishing when compared to heavier walk behind machines. Matched with multi-use combination blades and a variable-length pole, this unit achieves optimum control from up to 6 meters away and allows the operator to complete finishing works without the need to step foot on the wet concrete

- Blade pitch function of up to 25 degrees
- Allows for the PortaTrowel to be used for initial floating of the wet concrete right trough to final finishing
- Control from up to 6m away
- Variable length pole/stick for optimised control when finishing concrete (* Clip together handles sold separately)
- Easy Control directional steering function
- Allows for precise movement of the PortaTrowel by twisting the handle from side to side



- Lightweight design
- Improved operator comfort and safety
- Honda GX35 engine
- Hassle free operation
- Low engine emissions

Specifications :

- Trowel diameter: 750mm – 30"
- Operating weight: 20 kg
- Number of blades: 4
- Speed range: 40-70 RPM
- Blade pitch max: 25 deg
- Engine make: Honda
- Engine model: GX35
- Max rated power: 1.5 Hp
- Fuel type: petrol
- Shipping dimensions; 775x775x480 mm
- Shipping weight: 25 kg