

SHX Series(900 - 1500W)

Portable Gasoline Generators

SHX1000









FEATURES

- Advanced Technology

Newly designed Multi-pole Alternator and high speed engine dramatically reduced the size and weight.

- Honda 4-stroke Engine

Honda multi purpose engine has been industry standard for reliability and durability in the world. Also guaranteed with just a light pull on the recoil starter.

- Long Operating Hours

Large fuel tank allows efficient work without refueling.

These models are especially easy to carry.

- Lower Sound Level(Silent and Power mode)

This unique designed silent mode for SHX1000 provides extremely lower sound level with 3/4 load. Just in case to take full load, only to change to Power mode.

- Compact & Light Weight

The SHX1000 weighs only 13.6kg, The SHX2000 weighs only 21kg, less than half of the weight of similar capacity conventional generator.

SHX2000

















SPECIFICATIONS E-mail: info@famcocorp.com

🚳 w w w . f a m c o c o r p . c o m

@famco_group

(Tel:071- F A 0 0 0 0 F 9

Fax:∘۲1 - ۴۴99۴۶۴۲

نهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج) وبـروی پالایشگاه نفت پـارس، پلاک ۱۲

SHX Series

Models			SHX 1000				SHX 2000			
уре			R	G	S	L	R	G	S	L
Generator	Frequency (Hz)		50 60				50 60			
	Engine Speed (rpm)		5800/4100(Power Mode/Silent Mode)				4500			
	Waveform		Square-Wave							
	AC Output	Maximum Power (W)	1000				1900			
		Rated Power (W)	900				1500			
		Rated Voltage (V)	220	230	220	120	220	230	220	120
	DC Output		Only for Charging 12V Automotive Batteries.							
			Maximum Charging Output = 8.3/4.2 A(Power Mode/Silent Mode)				Maximum charging output = 8.3A			
	Insulation Class		В							
Engine	Maker		Honda							
	Models		GXH50				GX100			
	Туре		Air Cooled OHV 4-stroke Gasoline				Air Cooled OHC 4-stroke Gasoline			
	Displacement (CC)		49.4				98.5			
	L x W x H (mm)		465 x 265 x 380				560 x 340 x 415			
	Dry Weight (kg)		13.6	14.0	13.6	13.6	21.0	22.0	21.0	21.0
	Fuel Tank Capacity(litres)		3.8				7.7			
	Sound Level [dB(A)/7m]		58(1/2 load)				63(1/2 load)			
	[dB Lwa]		89(3/4 load)				93(3/4 load)			
	Continuous Operable Hours		5.5(rated load) 8.6(1/2 load)				7			
	Pilot Lamp		LED							
	Power Indicator		LED							
	Oil Alert System		YES							
	Engine Stop		Interlocking with Fuel Cock				Rocker Switch			
	AC	Output	Plug Socket x 1 Plug Socket x 2							
	-	Protective Device	Control Circuit							
	DC	Output	Terminal							
	Protective Device		Thermal Type Circuit Breaker							

- E-mail: info@famcocorp.com
- @famco_group

Теl:о۲1- к л о о о о к 9





SAWAFUJI GENERATORS
Proudly Made in Japan

ELENIAX

Power of Next Generation

SAWAFUJI ELECTRIC CO., LTD.



