

HISAKI

CONSTRUCTION EQUIPMENT CATALOGUE

- 🔞 w w w . f a m c o c o r p . c o m
- E-mail: info@famcocorp.com
- @famco_group

,0

- (Tel:011- F A 0 0 0 0 F 9
- (Fax:071 FF99F9FF

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

روبـروی پالایشگاه نفت پـارس، پلاک ۱۲

O'

















INTRODUCING

Jinhui Industries Sdn Bhd

Jinhui Industries Sdn Bhd (JHI) is a wholly owned subsidiary of Sin Yuan Enterprise Sdn Bhd, and belongs to the Sin Yuan Group specializing in the distribution of various light industrial, construction, food machinery, agriculture machinery and equipment.

The history of JHI can be traced back to 1976 when the founders of the Company started their business as a small machinery retailer. In line with

the business growth, JHI was set up to manufacture construction equipment that is widely used for infrastructure projects. The Company commenced operation in 1994 and has been accredited for the ISO9001 certification for Quality Management since 2000.

Prior to March 2002, JHI's principal activities comprise the manufacture of light machinery and equipment. Its products were distributed via its related company, Sin Yuan Machinery Sdn Bhd. The Company's main manufacturing products include plate compactor, concrete cutter, power trowel, concrete vibrator, submersible pump, bar bender, bar cutter, portable hoist, concrete manual fed mixer, concrete mini mixer, and generators.

Effective from March 2002, in tandem with the Group's business plans to

streamline its distribution activities, JHI took over the distribution business of construction equipment and pneumatic tools. Hence, other than its own manufactured products. JHI also imports equipment from Japan and Europe for onward distribution in

Currently, JHI has the largest local distribution network in Malaysia for light construction machinery and the main export markets are Middle East, Europe, Africa, South America and Asia. With the company vision of becoming the world-leading manufacturer of quality and value-formoney machineries, the Company has gained strong reputation for product quality and reliability both locally and internationally.



- w w w . f a m c o c o r p . c o m
- E-mail: info@famcocorp.com
- @famco_group

- (Tel:011- F A 0 0 0 0 F 9
- Fax:∘۲1 ۴۴99۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج) روبـروی پالایشگاه نفت پـارس، پلاک ۱۲



YTR81

- Heavy duty shock absorber to absorb kickback.
- Heavy shock absorber to reduce hard-arm vibration and improve operator's comfort.
- Oil bath lubrication system.
- · With yellow bellow.
- Rammer shoe made of steel plate with wooden insert offers economical usage. Steel made fuel tank to prevent easy damaged.
- Protective top frame cover eliminates possible damage to the engine.

Weight (kg)	81
Shoe Size L x W	324 x 300
Vibrating Frequency (vpm)	645 - 695
Vibration Stroke (mm)	50 - 80
Impact Force (kgf)	1680
Engine	Gasoline 5 hp / 3600 rpm
Max. Output (hp/rpm)	4.0/4000

YTR82

- Strong casting body to increase durability.
- Heavy duty shock absorber to absorb kickback.
- Heavy shock absorber to reduce hard-arm vibration and improve operator's comfort.
- Grease lubrication system.
- Rammer shoe made of steel plate with wooden insert offers economical usage.
- · With yellow bellow.
- Steel made fuel tank to prevent easy damaged.
- Protective top frame cover eliminates possible damage to the engine.

Weight (kg)	90
Shoe Size L x W	330 x 300
Vibrating Frequency (vpm)	570 ~ 600
Vibration Stroke (mm)	45 ~ 55
Impact Force (kgf)	1200
Engine	Robin EH12, 4 Stroke
Max. Output (hp/rpm)	4.0/4000



FAMCO هایپرسنعت

YCS200

- Machine can be set to a cutting depth and retain this depth after lifting or cornering, just by pulling up a quick lift lever, enabling the operator to resume work quickly and effortlessly.
- Adjustable handle for different operator height and easy storage.
- High carbon steel drive shaft and quality sealed bearings to ensure longer life.
- Accurate cutting depth adjustable with fine-tuning adjustment knob.
- Front mounted lifting handle and engine lifting bar provided for easy and safe handling.
- Anti vibration mounting to ensure operator's comfort.
- Powder coated finish for lasting appearance.
- Dust control outlet to minimize emission of dust particles during operation.
- Controls situated on handle for easy access.

Working Width (mm)	200
Max. Cutting Depth (mm)	3
Dimension L x W x H (mm)	905 x 400 x 1105
Cutter Speed (rpm)	2,600
TCT Cutter Quantity (pc)	76
Washer Quantity (pc)	84

