



CONTRACTOR ESSENTIALS
ContractorEssentials.com.au

CEI

FAMCO
هایپر صنعت

CEM BX-150

Dry-Well Temperature Calibrator



Visit our web store to buy it now : www.contractoressentials.com.au

Visit our website for more info: www.tmg.com.au



The Package Experts

- test equipment
- hand tools
- safety products
- consuma-

Free Call 1800 680 680

sales@tmg.com.au

www.famcocorp.com

E-mail: info@famcocorp.com

[@famco_group](https://www.facebook.com/famco_group)

Tel: ۰۲۱-۴ ۸ ۰ ۰ ۰ ۰ ۴ ۹

Fax : ۰۲۱ - ۴۴۹۹۴۶۴۲

تهران ، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

روبروی پالایشگاه نفت پارس ، پلاک ۱۲

BX-150

Dry-Well Temperature Calibrator

The new heat source to check your thermometer's accuracy up to 300°C/572°F. Simply set the heat source to the desired test point, insert the test probe into the best fitting well, and get a verification of the performance. It's that easy!

Features

Range	33°C to 300°C / 91.4°F to 572°F
Resolution	0.1°C/°F
Accuracy	±0.5°C(33 to 199°C) & ±1°C(200 to 300°C) ±0.9°F(91.4 to 390.2°F) & ±1°F(392 to 572°F)
Stability	±0.5°C
Heating Time	Ambient to 300°C(572°F) after 10 minutes
Cooling Time	300°C (572°F) to 100°C (212°F) after 10 minutes

Size (H x W x D): 180mm x 114mm x 233mm

Weight: 2200g

Specifications	BX-150
Range	33°C to 300°C / 91.4°F to 572°F
Resolution	0.1°C/°F
Accuracy	±0.5°C(33 to 199°C) & ±1°C(200 to 300°C) ±0.9°F(91.4 to 390.2°F) & ±1°F(392 to 572°F)
Stability	±0.5°C
Heating Time	Ambient to 300°C(572°F) after 10 minutes
Cooling Time	300°C (572°F) to 100°C (212°F) after 10 minutes
Stabilization	5 minutes
Well Depth	4"(100mm)
Power	230/115volts
Size (H*W*D)	180mm*114mm*233mm
Weight	2200g

Accessories: Box, AC power cable.

Dry-Well Temperature Calibrator

The new heat source to check your thermometer's accuracy up to 300°C/572°F. Simply set the heat source to the desired test point, insert the test probe into the best fitting well, and get a verification of the performance. It's that easy!

***CEM***