

WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY



BETON TROWEL n.v.

Tel. +32 (0)52 315 350

Tel. +32 (0)52 315 351

Fax +32 (0)52 315 359

info@betontrowel.com

www.betontrowel.com

Nijverheidsstraat 10

BE-1840 Londerzeel - Belgium

**BTCS350H
CONCRETE &
ASPHALT SAW**



- Easy to transport. Very light weight facilitating transport and handling.
- Adjustable handle and extendable right rear wheel for increased stability.
- Low vibrations. Engine and blade shaft mounting system increases comfort and gives excellent cutting performance.
- Low maintenance. The sealed blade shaft system allows for a minimum of 200 maintenance-free hours without daily greasing of bearings.
- Adjustable handles. Provides a closer and more comfortable position to the cutting side for easier alignment and straighter cuts. Handle can also be folded for transport.
- Clear depth indicator.



Specifications :

- Engine : Honda GX270
- Max Power : 9 HP (6.4 kW)
- Fuel Capacity : 6 l
- Operating speed : 3600 RPM
- Dimensions
 - Length : 915 mm
 - Height : 990 mm
 - Width : 380 mm
- Weight : 69 kg
- Max Blade diam. : 350 mm
- Max cutting depth : 120 mm
- Depth control : Handle rotation
- Water tank capacity : 15 l

WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY

BTCS500H
CONCRETE &
ASPHALT SAW

BETON TROWEL n.v.

Tel. +32 (0)52 315 350

Tel. +32 (0)52 315 351

Fax +32 (0)52 315 359

info@betontrowel.com

www.betontrowel.com

Nijverheidsstraat 10

BE-1840 Londerzeel - Belgium



A strong powerful machine for Green Concrete cutting and all types of repair work on both Concrete & Asphalt surfaces.

- Design of the water tank changes the centre of gravity of the machine when lowering the blade for cutting giving just the right amount of pressure to the blade for maximum cutting effect.
- Recessed rear wheels making a cut long an open trench simple
- Rigid front pointer to assist straight accurate cut
- Easy and accurate handling
- Easy maintenance

Specifications :

- Engine : Honda GX390 13 HP (9.6 Kw)
- Starter : Recoil
- Max Blade : 500mm
- Blade Bore : 25.4mm
- Max depth : 190mm
- Blade speed : 2600 rpm
- Drive Belts : 4
- Water Tank : 70 L
- Waterflow : Dual sides of the blade
- Dimensions :
L 1088
W 580
H 925mm
- Dry weight : 140 Kg
- Max weight : 220 Kg
- Sound Pressure 89 LPA (Db)
- Sound Energy 105 LWA (dB)
- Hand arm vibration: 4.22m/s²



WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY

BTCS501



BETON TROWEL n.v.

Tel. +32 (0)52 315 350

Tel. +32 (0)52 315 351

Fax +32 (0)52 315 359

info@betontrowel.com

www.betontrowel.com

Nijverheidsstraat 10

BE-1840 Londerzeel - Belgium

SAW

- Low vibrations. Engine and blade shaft mounting system increases comfort and gives excellent cutting performance.
- Low maintenance. The sealed blade shaft system allows for a minimum of 200 maintenance-free hours without daily greasing of bearings.
- Easy to adjust the blade. Spring-assisted screw feed facilitates blade adjustment in and out of the cut.
- Adjustable handles. Provides a closer and more comfortable position to the cutting side for easier alignment and straighter cuts. Handle can also be folded for transport.
- Clear depth indicator.

Technical specifications

Max Power	kW/hp	8.7/13
Fuel capacity	L	6.1
Weight	Kg	163
Dimensions (LxWxH)	mm	1550x655x1200
Max. blade diameter	mm	500
Max. cutting depth	mm	185
Water tank capacity	L	18

