

# RB260GS series



The RB260GS is a small SOHO switch. Two models are available, the RB260GS, and the RB260GSP, which features power output on its ethernet ports. Ports 2-5 can power other PoE capable devices with the same voltage as applied to the unit.

Both devices have five Gigabit Ethernet ports and one SFP cage, switching is done by an Atheros Switch Chip.

The devices are running an operating system designed specifically for MikroTik Switch products - SwOS.

SwOS is configurable from your web browser. It gives you all the basic functionality for a managed switch, plus more: Allows to manage port-to-port forwarding, apply MAC filter, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields.

Tested and recommended to use with MikroTik SFP modules: S-85DLC05D, S-31DLC20D and S-35/53LC20D (not included)

CPU	Taifatech TF470
Memory	Embedded 96K SRAM
Ethernet	Five 10/100/1000 Ethernet ports, Atheros switch AR8327
PoE output	RB260GSP only: Passive PoE output on ports 2-5. Max current 1A per port
SFP	One fixed Gigabit Ethernet SFP cage with DDMI support (Mini-GBIC; SFP module not included)
Serial port	No serial port
LEDs	Power, NAND activity, 5 Ethernet activity LEDs
Extras	Hardware watchdog
Power options	PoE: 8-30V DC on Ether1 (Non 802.3af). Jack: 8-30V DC
Dimensions	113x138x29mm. Without packaging and PSU: 212g
Power consumption	Up to 6W
Operating Temperature	-25C .. +65C
Operating System	MikroTik SwOS