

● **TILLER AND CULTIVATOR SERIES**
● **TIMÓN Y SERIES CULTIVADOR**
● **BARRE ET SÉRIE CULTIVATEUR**

- ★ Powerful output, easy operation and maintenance.
- ★ Compact structure, small size, light weight and excellent functions.
- ★ Widely used in field work such as cultivation, ditching and earthing up, etc, also in large shed vegetable base, paddy field, dry farmland and sandy land.
- ★ Easy operation: Circum-cultivation, deep or shallow ploughing, the height of the handle and the depth of the ploughing are adjustable.
- ★ Weima has the widest range of tiller models in the Chinese market.



WM400B

Powered by 1P64F/P, this tiller has the same performance and function as WM400.



WM500

Belt transmission, powered by WM168FB/P gasoline engine of 6.5HP. Suitable for different land usage.

WM500AMF

Belt transmission, powered by WM168FB/P gasoline engine of 6.5HP. Suitable for different land usage with 360 degree rotary handle bar.



WM900-2

Powered by gasoline engine WM168FB/P, it has a good reputation for its excellent function and performance.



WM1050

Belt transmission, unique design, powered by WM168FB/P gasoline engine of 6.5Hp.



WM1000(A)

All gear transmission, powered by WM168FB-2/P gasoline engine of 6.5Hp. Suitable for different land usage with 360 degree rotary handle bar.

WM1000N

Rotary tilling machine is powered by WM168FB-2/P gasoline engine.



SPECIFICATION

Model	WM400B	WM500	WM500AMF	WM900	WM1000(A)	WM1000N	WM1050
Body size(mm)	1400 × 700 × 980	1360 × 650 × 970	1380 × 650 × 970	1390 × 800 × 1070			
Tilling scope(mm)	700	900	600	1050	700	700-1050	1050
Tilling depth(mm)	150-250	150-300	150-300	150-300	150-300	150-300	150-300
Gear shifting	1	1/2,0,1/-1,0,1/-1,2,0,1	-1,1	1/2,0,1/-1,0,1/-1,2,0,1	1,2,3,-1,0	1,0,2-1	-1,2,0,1
Driving model	gear	Belt	Belt	Belt	gear	gear	belt
Max.torque(N.m/rpm)	6.8/2500	11/2500	11/2500	11/2500	11/2500	11/2500	11/2500
Transmission oil capacity(L)	0.6	0.95	0.95	1.1	0.6	1.1	1.1
Engine model	WM1P65F/P	WM168FB/P	WM168FB/P	WM168FB-2/P	WM168FB-2/P, Q shaft	168FB-2/P /170F-2/P	WM168FB (speed- down equipment. 44%)
Max.power hp(kw)/rpm	5(3.7)/3800	6.1(4.5)/3800	6.1(4.5)/3800	6.1(4.5)/3800	6.1(4.5)/3800	4.2(3.1)/3800	6.1(4.5)/3800
N.W/G.W(kg)	30/35	60/74	60/74	70/85	95/100	211/298	82/95
Dimension(mm)	720 × 440 × 740	820 × 375 × 780	885 × 380 × 770	880 × 410 × 780	870 × 455 × 720	890 × 455 × 780	890 × 455 × 660
20FT(Set)	126	125	125	96	96	96	98
Certificate	CE	CE/GS	CE	CE	CE		CE



TILLER SERIES

FAMCO
هایپر صنعت



Normally disengaged clutch



Standard Handle



WM1100 SERIES



With battery



Diesel engine



With water pump



Trailer

Matching model: WM1100A, WM1100B series

www.famcocorp.com
E-mail: info@famcocorp.com
@famco_group

Tel: ۰۲۱-۴۸۰۰۰۰۴۹
Fax: ۰۲۱-۴۴۹۹۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)
روبروی پالایشگاه نفت پارس، پلاک ۱۲



WM1100A(E)
WM1100B(E)

Powered by diesel engine with great output, they can make your field work easier.

SPECIFICATION

	Model	WM1100A(E)	WM1100B(E)	WM1100C	WM1100D(E)
TILLER	N.W / G.W	115/120	135/140	110/125	115/120
	Tilling width(mm)	800-1100	800-1300	800-1100	800-1100
	Tilling depth(mm)	150-300	150-300	150-300	150-300
	Gear shifting	1,0,2,-1	1,0,2,-1	1,0,2,-1	1,0,2,-1
	Driving model	gear	gear	gear	gear
ENGINE	Engine model	WM178F(Diesel engine)	WM168FB(Diesel engine)	WM168FB-2/P	WM177F/P
	BorexStroke(mm)	78 x 62	86 x 70	68 x 54	77 x 58
	Displacement(ml)	296	406	211	277
	Max.output hp(kw)/rpm	6(4.4)/3600	9(6.6)/3600	6.1(4.5)/3600	9(6.5)/3600
	Rated power hp(kw)/rpm	5.3(4)/3600	8.4(6.3)/3600	8.4(6.3)/3600	6.7(5.0)/3600
	Fuel tank capacity(L)	3.5	5.5	3.6	6
	Lube capacity(L)	1.1	1.65	0.8	1.1
	Starting model	Recoil/Electric	Recoil/Electric	Recoil	Recoil/Electric
PACKING	Dimension	1050 x 570 x 780	1050 x 570 x 780	930 x 570 x 760	1050 x 570 x 780
	20FT(set)	66	66	66	66
	Certificate	CE	CE		