



UT380 series light meters measure light intensity and display results in Lux or Fc. It has a high sampling rate of 100/s. UT380 series' low power consumption allows up to 200 hours of continuous operation. Results can be stored within the device and transferred to PC for further analysis, printing and storage.

SPECIFICATIONS

	Range	UT381	UT382
Illuminance measurement (Lux)	20 Lux	±(3%+20)	±(3%+20)
	200 Lux	±(3%+8)	±(3%+8)
	2000 Lux	±(3%+8)	±(3%+8)
	20000 Lux	±(3%+8)	±(3%+8)
Illuminance measurement (Fc)	2 Fc	√	√
	20 Fc	√	√
	200 Fc	√	√
	2000 Fc	√	√

Features

Display count		2000	2000
Auto range		√	√
Data hold		√	√
Auto power off	Around 10 minutes	√	√
Low battery indication	Around ≤7.1V	√	√
MAX/MIN mode		√	√
Data storage		2044	2044
USB interface			√
Auto record time setup		√	√
Real-time clock		√	√



● UT382

GENERAL CHARACTERISTICS

Power	9V battery (6LF22)
Display	22.5mm x 32.5mm
Product color	Red and grey
Product net weight	185g
Product size	195mm x 45mm x 26mm
Standard accessories	Carrying bag, USB interface cable (UT382), PC software CD (UT382)
Standard individual packing	Blister, gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	447mm x 300mm x 335mm
Standard carton gross weight	7kg



UT383/UT383BT can effectively measure light intensity and display results in units of Lux or FC on screen. UT383BT can transfer measurement data through bluetooth to UNI-T's custom mobile APP (iENV) for further analysis, storage, and export. iENV can be downloaded from Google Play, Apple Store, or UNI-T's website by searching 'iENV'.

SPECIFICATIONS

	UT383	UT383BT
Illuminance measurement (LUX)	0~199,900Lux	0~199,900Lux
Illuminance measurement (FC)	0~18,500Fc	0~18,500Fc
Accuracy	0~9999Lux/0~999Fc: ±(4%+8)	
	≥10000Lux/≥1000Fc: ±(5%+10)	
	≥100000Lux/≥9999Fc: ±(5%+10)	
Resolution	1Lux (0~9999Lux)	
	10Lux (≥10,000Lux)	
	100Lux (≥100,000Lux)	
	1Fc (0~9999Fc); FC=Lux/10.76	
Sampling time	10Fc (≥10,000Fc); FC=Lux/10.76	
	0.5s	
Features		
APP		√
Bluetooth®		√
Overload indication	OL	OL
MAX/MIN	√	√
Data hold	√	√
LCD backlight	√	√
Auto power off	√	√
Low battery indication	√	√
Tripod mounting hole		√



● UT383 BT

GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 3
Display	32mm x 26mm
Product color	Red and grey
Product net weight	118g
Product size	160mm x 50mm x 28mm
Standard accessories	Batteries
Standard individual packing	Blister, English manual
Standard quantity per carton	UT383: 40pcs; UT383 BT: 20pcs
Standard carton measurement	UT383: 505mm x 330mm x 280mm UT383 BT: 332mm x 262mm x 290mm
Standard carton gross weight	UT383: 8.42kg; UT383 BT: 4.2kg

UT383S Digital Light Meter



- Split probe
- Sampling time: 0.5s
- Auto range
- Lux/Fc selectable
- Max/Min
- Overload indication (LO/HI)
- Data hold
- Backlight
- Auto power off
- Low battery indication

Applications:

Public settings, light manufacturing, photo studios, interior renovation, construction, greenhouses.

SPECIFICATIONS

	Range	Resolution	Accuracy
Illuminance	0~199,900Lux	1Lux (0~9999Lux)	±(4%+8)
		10Lux (≥10,000Lux)	±(5%+10)
		100Lux (≥100,000Lux)	±(5%+10)
		0.1Fc (0~999.9Fc)	FC=Lux/10.76
		1Fc (≥1000Fc)	
		10Fc (≥10,000Fc)	

Features

MAX/MIN	√
Data hold	√
Overload indication	√
Backlight	√
Auto power off	√

GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 3
Display	35mm x 32mm
Product color	Red and grey
Product net weight	300g
Product size	110mm x 53mm x 26mm
Standard accessories	Batteries
Standard individual packing	Blister, gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	560mm x 300mm x 335mm
Standard carton gross weight	6.9kg