













HiLook Analog Solution
Turbo HD Camera / Turbo HD DVR

1	THC-B340-VF		4MP high-performance CMOS Sensor - 2.8-12mm Vari Focal Lens , EXIR Bullet, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR, OSD Menu, IP66 , Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal
2	THC-B240-M		4MP high-performance CMOS Sensor, EXIR Bullet, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR-DWDR, OSD Menu, IP66 , 2.8mm Lens ,Support HD-TVI/AHD/CVI/CVBS video output-Full Metal
3	THC-B240		4MP high-performance CMOS - 2560 ×1440 resolution- 2.8 mm - fixed focal lens-Day/Night switch- EXIR 2.0 , smart IR, up to 40 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - DWDR-BLC-IP 66
4	THC-B140-M		4MP high-performance CMOS - 2560 ×1440 resolution- 2.8 mm - fixed focal lens-Day/Night switch- EXIR 2.0 , smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - DWDR-IP 66-BLC-Full Metal
5	THC-B140-P		4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0 , smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66
6	THC-B320-VF		2MP high-performance CMOS Sensor, 40m IR , Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR,,DWDR- DNR, OSD Menu, IP66 , 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal
7	THC-B220-M		2MP high-performance CMOS Sensor, 40m IR , Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66 , 2.8 mm Lens , Support HD-TVI/AHD/CVI/CVBS video output-Full Metal
8	THC-B220		2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens-Day/Night switch- EXIR 2.0 , smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66

9	THC-B120-M		2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm ,fixed focal lens-Day/Night switch- EXIR 2.0 , smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66-METAL	
10	THC-B120-P		2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm ,fixed focal lens-Day/Night switch- EXIR 2.0 , smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	
11	THC-D340-VF		4MP high-performance CMOS Sensor, EXIR Dome, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu , IP66, 2.8-12mm Vari Focal Lens,IK10 , Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	
12	THC-T340-VF		4MP CMOS Sensor, EXIR Eyeball, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu , IP66, 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic-Eyeball: Metal	
13	THC-T240-M		4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0 , smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66-METAL	
14	THC-T240-P		4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0 , smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66	
15	THC-T140-M		4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm , Fixed focal lens-Day/Night switch- EXIR 2.0 , smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66-METAL	
16	THC-T140		4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm , Fixed focal lens-Day/Night switch- EXIR 2.0 , smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66	
17	THC-T140-P		4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm , Fixed focal lens-Day/Night switch- EXIR 2.0 , smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)DWDR-BLC-IP66	
18	THC-D320-VF		2MP high-performance CMOS Sensor, 40m IR, EXIR Dome , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu , IP66, 2.8-12mm Vari Focal Lens--support HD-TVI/AHD/CVI/CVBS video output-, IK10-Full Metal	

19	THC-T320-VF		2MP high-performance CMOS Sensor, 40m IR , EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR-OSD Menu , IP66, 2.8-12mm Vari Focal Lens , Support HD-TVI/AHD/CVI/CVBS video output- Cover&Base:Plastic- Eyeball: Metal	
20	THC-T220-M		2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm ,fixed focal lens-Day/Night switch- EXIR 2.0 , smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	
21	THC-T220-P		2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm ,fixed focal lens-Day/Night switch- EXIR 2.0 , smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	
22	THC-T120-M		2 MP high-performance CMOS- 1920 × 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	
23	THC-T120		2 MP high-performance CMOS- 1920 × 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	
24	THC-T120-P		2 MP high-performance CMOS- 1920 × 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	