**CONCRETE & ASPHALT CUTTER** 

CCG270M / CCG390M / CCG390A / CCG630A

CCG-SERIES are designed for strength, durability and performance.

Whether cutting concrete or asphalt, the reinforced steel box frame design adds strength necessary to reduce vibrations while sawing.

Minimizing vibrations enhances the performance of the blade extends the life of the saw.



- · Designed for excellent strength, good durability and performance
- · Suitable for cutting concrete or asphalt, the reinforced steel box frame
- . Design adds strength necessary to reduce vibrations while sawing
- · Comfortable grip handle
- · Easy adjust belt tension / easy belt replacement
- Designed to provide easy blade & belt replacement
- · Saw position guide ensures straight cutting
- · Water tank provides optimum water flow to the blade
- · Urethane wheel for easy transportation
- Throttle lever for easy control of cutting speed
- · Japanese shatt bearing for long service life

## Diamond blades





### **Product Views**














- w w w . f a m c o c o r p . c o m
- E-mail: info@famcocorp.com
- @famco\_group





PUSH-MANUAL & WHEEL DRIVE TYPE

# **CONCRETE & ASPHALT CUTTER**

CCG270M / CCG390M / CCG390A / CCG630A



Push-manual cutting type CCG-270M 9.0hp (6.75kw) CCG-390M 13.0hp (9.75kw)



Wheel drive cutting type CCG-390A 13.0hp (9.75kw) CCG-630A 20.8hp (15.5kw)

COHER SUBARU A LOMBARDINI

- · Cutting surface of asphalt and concrete loads, paking lots, ground of shopping center,
- Cutting block and stones
- · Repair works for Pipe line construction
- · Repair works for asphalt construction

## Option

- Available diamond blade (10"~20")
- · Electric starter with battery
- · Engine (Available engine model as below)

## Available Engine







GX630 (20.8HP) GX390 (13.0HP) GX270 (9.0HP)

Specifications

MODEL		CCG-270M	CCG-390M	CCG-390A	CCG-630A
WEIGHT	Kg/lb	110/242	117 / 257	121/266	134 / 296
DIMENSION (W) X (L) X (H)	mm / inch	610×1540×1040 24.0×60.6×40.9	610×1540×1040 24.0×60.6×40.9	630×1540×1040 24.8×60.6×40.9	630×1540×1040 24.8×60.6×40.9
MAX. CUTTING DEPTH		10" ~ 16"	10" ~ 18"	10"~18"	10" ~ 20"
DRIVE METHOD		PUSH-MANUAL	PUSH-MANUAL	WHEEL DRIVE TYPE	WHEEL DRIVE TYPE
WATER TANK	1/gal	27.6 / 7.29	27.6 / 7.29	28.2 / 7.44	28.2 / 7.44
STARTER		RECOIL STARTER (OPTION: ELECTRIC STARTER)		ELECTRIC STARTER	
ENGINE					
BRAND		HONDA	HONDA	HONDA	HONDA
MODEL		GX270	GX390	GX390	GX630
TYPE		AIR-COOLED 4-CYCLE		AIR COOLED 4-CYCLE	
FUEL		GASOLIINE		GASOLIINE	
OUTPUT	Hp / KW	9.0 / 6.7	13.0 / 9.75	13.0 / 9.75	20.8 / 15.5
SPEED	RPM	3,600	3,600	3,600	3,600
TANK CAPACITY	gal	6.0 / 1.6	6.0 / 1.6	6.0 / 1.6	15 / 4.0
WEIGHT	Kg/lb	25/55	31 / 68.2	31 / 68.2	44.4 / 97.7

روبـروی یالایشگاه نفت یـارس، یلاک ۱۲