

WEIMA

DIESEL GENERATOR

WEIMA GENERAL POWER MACHINERY
PRODUCTS SERIES

WM3600CL



Feature introduction

- Distinguished and smooth appearance
- 100% copper high efficiency alternator, new AVR for stable output and quality energy
- Overload, over-current protection protect the generator from damage
- High quality electric components allows stable quality and reliable performance
- Shock absorb support shelf reduces vibration and prolong life
- Square frame design allows better strength
- High strength 4-wheel structure for easy transportation
- Various optional specifications
- Manual/Electric start optional
- Low oil protection system allows automatic shutoff when low oil is detected
- 50HZ/60HZ optional
- 120V/230V/240V/400V

Model	WM3600C	WM5000C(E)	WM7000C(E)	WM8000C(E)	WM10000C(E)
Rated frequency(Hz)	50/60	50/60	50/60	50/60	50
Rated power(kw)	2.8/3.2	4.5/5.0	6.0/6.5	6.5/7	8
Max.AC Output(kw)	3.2/3.5	5/5.5	6.5/7	7.0/7.5	8.5
Starting system	Recoil		Recoil/Electric Start		Electric Start
Rated voltage(V)		110, 120, 220, 230, 240			230/240
Engine type		single-cylinder, 4-stroke, forced air-cooling, direct injection diesel engine			
Engine model	WM178F	WM186FB (E)	WM192F(E)	WM195F(E)	WM1100FE
Displacement (cc)	296	418	498	532	667
Fuel capacity(L)	15	16	16	16	25
Dimension (L×W×H) mm	675×500×565	715×530×605	715×530×605	750×600×625	800×580×800
*Packing Dimension (L×W×H) (mm)	730×560×610	730×560×670	730×560×670	765×630×690	815×600×810
Loading capacity/40HQ	256	192	192	162	156
N.W/G.W	65/68	92/95	98/113	106/125	142/162

Diesel Generator

www.famcocorp.com

E-mail: info@famcocorp.com

@famco_group

Tel: ۰۲۱-۴۸۰۰۰۰۴۹

Fax: ۰۲۱-۴۴۹۹۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

روبروی پالایشگاه نفت پارس، پلاک ۱۲