

WORLD BEATING PRODUCT LINE

WORLD CLASS QUALITY

FAMCO
هایپر صنعت



BETON TROWEL n.v.

tel. +32 (0)52 315 350

tel. +32 (0)52 315 351

fax +32 (0)52 303 739

info@betontrowel.com

www.betontrowel.com

Nijverheidsstraat 11

B-1840 Londerzeel - Belgium



**CONCRETE
VIBRATOR
HUMDINGER**

Humdinger Electric Flexible Shaft Concrete Vibrators

- Powerful Lightweight electric Power unit with robust motor protection
- Variety of Flexible shaft lengths from 1m to 6m
- Double insulated 2.3 Kw motor with 230v and 115v options.
- Motors and Vibrators interchangeable with other leading brands



Model		Voltage	Kw	Hz	Motor Speed	weight
HVU110	Humdinger Electric Power Unit	115v	2,3	50/60	18000	5.5 Kg
HVU220	Humdinger Electric Power Unit	230v	2,3	50/60	18000	5.5 Kg

Model	Vib diam	Length	Weight	Frequency	Amplitude
HDV25/2	25mm	2m	5.50 Kg	14000	1,12
HDV25/6	25mm	6m	8.50 Kg	14000	1,12
HDV28/6	28mm	6m	9.40 Kg	13700	1,20
HDV38/1	38mm	1m	4.96 Kg	13500	1,41
HDV38/2	38mm	2m	6.26 Kg	13500	1,41
HDV38/3	38mm	3m	7.56 Kg	13500	1,41
HDV38/4	38mm	4m	8.86 Kg	13500	1,41
HDV38/5	38mm	5m	10.36Kg	13500	1,41
HDV38/6	38mm	6m	11.86 Kg	13500	1,41
HDV48/3	48mm	3m	8.90 Kg	12750	1,65
HDV48/4	48mm	4m	10.20 Kg	12750	1,65
HDV48/5	48mm	5m	11,70 kg	12750	1,65



BT CONCRETE VIBRATORS

BT45H PORT-A-VIBE

THE **PORT-A-VIBE** PROVIDES
AN **EASY SOLUTION TO
VIBRATING CONCRETE
FLOORS AND FOUNDATION
FOOTINGS**. BEING TOTALLY
SELF CONTAINED, THERE ARE
NO CABLES OR LONG FLEXIBLE
SHAFTS TO DRAG THROUGH
THE CONCRETE

Head diameter: 45mm
Frequency: 9000 bpm
Amplitude: 2.8mm
Weight: 11kg



- Reliable Honda GX35 4 stroke petrol engine
- Well-balanced unit with a carry strap for ease of operation
- Good balance of amplitude and frequency for efficient compaction of the concrete and elimination of air voids

