



**DAEWOO**

POWER PRODUCTS

*Power your Skills*

## PRODUCTS CATALOGUE





- POWER PRODUCTS
- VOLTAGE STABILIZERS
- HEATERS



## PRODUCTS CATALOGUE



www.famcocorp.com  
E-mail: info@famcocorp.com  
@famco\_group

www.famcocorp.com  
E-mail: info@famcocorp.com  
@famco\_group  
Tel: 021-44994642  
Fax: 021-44994642

Tel: 021-44994642  
Fax: 021-44994642



100%  
*Daewoo*  
power

Control voltage  
by capacitor

Low Oil  
Alert



Air  
filter

**GDA980 0.8 kW**

**Engine type:** Air cooler/2 Stroke/  
Single Cylinder  
**Max output :** 800 W  
**Rated output:** 680 W  
**Displacement:** 63 cm<sup>3</sup>  
**Fuel tank capacity:** 4.2 L  
**Oil/Fuel mixture:** 1:50  
**Includes:** Spark plug wrench

Appliances Table

TYPICAL USE	LIGHT BULB	FAN	SUMP PUMP 1/2 HP	KITCHEN APPLIANCE	RADIO	SPACE HEATER	FRIDGE
RUNNING	100	200	1000	750	200	1000	500
ADDITIONAL WATTS REQUIRED TO START	0	0	1000	0	0	0	500

TYPICAL USE	CELL PHONE CHARGER	GARAGE DOOR OPENER	SECURITY SYSTEM	AC UNIT	FURNACE FAN 1/2 HP/	MICROWAVE	WELL PUMP 1/2 HP
RUNNING	10	550	100	1200	900	800	1000
ADDITIONAL WATTS REQUIRED TO START	0	550	0				

www.famcocorp.com  
E-mail: info@famcocorp.com  
@famco\_group

Tel: ۰۲۱-۴۸۰۰۰۰۴۹  
Fax: ۰۲۱-۴۴۹۹۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)  
روبروی پالایشگاه نفت پارس، پلاک ۱۲

Grip  
Transportation  
handle



Front  
panel

Never flat PVC  
8" Wheels

Air  
filter

**GDA3050/E 2200 W**

**Rated power:** 2000 W  
**Max power:** 2200 W  
**Displacement:** 212 cc  
**Starting System:** Recoil / Electric  
**Oil tank capacity:** 0.6 L  
**Fuel tank capacity:** 15 L  
**Phase:** Single  
**Circuit breaker:** 8.7 A/ 1 P  
**Includes:** Spark Plug

**GDA4650/E 3000 W**

**Rated power:** 2800 W  
**Max power:** 3000 W  
**Displacement:** 212 cc  
**Starting system:** Recoil / Electric  
**Oil tank capacity:** 0.6 L  
**Fuel tank capacity:** 15 L  
**Phase:** Single  
**Circuit breaker:** 16 A/ 2 P  
**Includes:** Spark Plug

ALL  
GENERATORS  
INCLUDES



Spark Plug Wrench Oil Alarm Light DC 12V



ALSO AVAILABLE WITH  
ELECTRIC START AND 3-PHASE



**5400 W** ⚡

**GDA7750/E/-3**

**Rated power:** 5000 W  
**Max power:** 5400 W  
**Displacement:** 420 cc  
**Starting system:** Recoil / Electric  
**Oil tank volume:** 1.1 L  
**Fuel tank capacity:** 25 L  
**Circuit braker:** 21.7 A / 1 P  
**Phase:** Single phase / Three phase  
**Spark plug wrench:** Yes

**6500 W** ⚡

**GDA9250/E/-3**

**Rated power:** 6000 W  
**Max power:** 6500 W  
**Displacement:** 420 cc  
**Starting system:** Recoil / Electric  
**Oil tank volume:** 1.1 L  
**Fuel tank capacity:** 25 L  
**Circuit braker:** 26.1 A / 1 P  
**Phase:** Single phase / Three phase  
**Spark plug wrench:** Yes

**7900 W** ⚡

**GDA11050/E/-3**

**Rated power:** 7500 W  
**Max power:** 7900 W  
**Displacement:** 457 cc  
**Starting system:** Recoil / Electric  
**Oil tank volume:** 1.1 L  
**Fuel tank capacity:** 25 L  
**Circuit braker:** 32.6 A / 1 P  
**Phase:** Single phase / Three phase  
**Spark plug wrench:** Yes

⚡ **Daewoo Power Energy everywhere**

Specially designed to be one of the most valuable tools at home or work. From 800 VA to 15 KVA, lack of electricity will not be a problem anymore. Useful to power different kind of applications, in a camping or at home. All generators include AVR technology, which ensures a consistent flow of power, with larger fuel tanks for you to run them up to 18 hs with one full load. Available with manual

www.famcocorp.com  
E-mail: info@famcocorp.com  
@famco\_group

Tel: ۰۲۱-۴۸۰۰۰۰۴۹  
Fax: ۰۲۱-۴۴۹۹۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)  
روبروی پالایشگاه نفت پارس، پلاک ۱۲



**GDA15000E**

**12000 W** ⚡

**Engine type:** 2 Cylinders, 4 Stroke, OHV, Air cooled  
**Rated power:** 11000 W  
**Max power:** 12000 W  
**Displacement:** 713 cc  
**Starting system:** Electric  
**Oil tank volume:** 1.6 L  
**Fuel tank capacity:** 40 L  
**Level sound at 7 m:** 79 dB  
**Low oil auto-stop system:** Yes  
**Spark plug wrench:** Yes

**GDA15000E-3**

**15000 W** ⚡

**Voltage/Frequency:** 380 V~50 Hz  
**Engine type:** 2 Cylinders, 4 Stroke, OHV, Air cooled  
**Rated power:** 13700 W  
**Max power:** 15000 W  
**Displacement:** 713 cc  
**Starting system:** Electric  
**Oil tank volume:** 1.6 L  
**Fuel tank capacity:** 40 L  
**Level sound at 7 m:** 79 dB  
**Low oil auto-stop system:** Yes  
**Spark plug wrench:** Yes

## Diesel Generators Ddae Series



**DDAE6000XE**

**5.0 kW** ⚡

**Engine type:** Air-cooled/ Vertical Single cylinder  
**Rated power:** 4.5 kW  
**Max power:** 5.0 kW  
**Displacement:** 418 cc  
**Starting system:** Electric Start  
**Oil tank volume:** 1.65 L  
**Fuel tank capacity:** 14 L  
**Oilt type:** SAE 10 W 30 15W  
**Max noise level at 7 m:** 78-83 dB  
**AC Voltage/DC Protector:** 12 V-20.5 A

**DDAE6000XE-3**

**5.0 kW** ⚡

**Voltage/Frequency:** 380 V~50 Hz  
**Engine type:** Air-cooled/ Vertical Single cylinder  
**Rated power:** 4.5 kW  
**Max power:** 5.0 kW  
**Displacement:** 418 cc  
**Starting system:** Electric Start  
**Oil Tank volume:** 1.65 L  
**Fuel tank capacity:** 14 L  
**Oilt type:** SAE 10 W 30 15W  
**Max noise level at 7 m:** 78-83 dB  
**AC Voltage/DC Protector:** 12 V-20.5 A



**DDAE9000XE**

**5.8 kW** ⚡

**Engine type:** Air-cooled/ Vertical Single cylinder  
**Rated power:** 5.5 kW  
**Max power:** 5.8 kW  
**Displacement:** 477 cc  
**Starting system:** Electric Start  
**Oil tank volume:** 1.65 L  
**Fuel tank capacity:** 14 L  
**Oilt type:** SAE 10 W 30 15W  
**Max noise level at 7 m:** 78-83 dB  
**AC Voltage/DC Protector:** 12 V-25 A  
**Tool kit:** Yes

**DDAE9000XE-3**

**6.0 kW** ⚡

**Voltage/Frequency:** 380 V~50 Hz  
**Engine type:** Air-cooled/ Vertical Single cylinder  
**Rated power:** 5.5 kW  
**Max power:** 5.8 kW  
**Displacement:** 477 cc  
**Starting system:** Electric Start  
**Oil Tank Volume:** 1.65 L  
**Fuel tank capacity:** 14 L  
**Oilt type:** SAE 10 W 30 15W  
**Max noise level at 7 m:** 78-83 dB  
**AC Voltage/DC Protector:** 12 V-25 A  
**Tool kit:** Yes



## Gid Series



### GD1000 1000 W

**Rated power:** 850 W  
**Max power:** 1000 W  
**Displacement:** 93.5 cc  
**Starting system:** Recoil  
**Oil tank volume:** 0.37 L  
**Fuel tank capacity:** 6 L  
**Low oil sensor:** Yes  
**Ignition system:** T.C.I.  
**Insulation class:** F  
**Phase:** Single phase

### GD2500 2200 W

**Rated power:** 2000 W  
**Max power:** 2200 W  
**Displacement:** 196 cc  
**Starting system:** Recoil  
**Oil tank volume:** 0.6 L  
**Fuel tank capacity:** 15 L  
**Ignition system:** T.C.I.  
**Insulation class:** F  
**Phase:** Single phase



### GD3500/-E 2800 W

**Rated power:** 2500 W  
**Max power:** 2800 W  
**Displacement:** 208 cc  
**Starting system:** Recoil/Electric  
**Oil tank volume:** 0.6 L  
**Fuel tank capacity:** 15 L  
**Insulation class:** F  
**Phase:** Single phase



www.famcocorp.com  
 E-mail: info@famcocorp.com  
 @famco\_group

Tel: ۰۲۱-۴۸۰۰۰۰۴۹  
 Fax: ۰۲۱-۴۴۹۹۴۶۴۲

### GD6500/-E 5500 W

**Rated power:** 5000 W  
**Max power:** 5500 W  
**Displacement:** 389 cc  
**Starting system:** Recoil/Electric  
**Oil tank volume:** 1.1 L  
**Fuel tank capacity:** 25 L  
**Ignition system:** T.C.I.  
**Insulation class:** F  
**Phase:** Single phase  
**Wheels:** 8" never flat PVC wheels  
**Spark plug wrench:** Yes

### GD7000/-E 6500 W

**Rated power:** 6000 W  
**Max power:** 6500 W  
**Displacement:** 420 cc  
**Starting system:** Recoil/Electric  
**Oil tank volume:** 1.1 L  
**Fuel tank capacity:** 25 L  
**Low oil sensor:** Yes  
**Excitation type:** Self-excitation  
**Insulation class:** F  
**Phase:** Single phase  
**Wheels:** 8" never flat PVC wheels  
**Spark plug wrench:** Yes

### GD8500/-E 7500 W

**Rated power:** 7000 W  
**Max power:** 7500 W  
**Displacement:** 439 cc  
**Starting system:** Recoil/Electric  
**Oil tank volume:** 1.1 L  
**Fuel tank capacity:** 25 L  
**Low oil sensor:** Yes  
**Excitation type:** Self-excitation  
**Insulation class:** F  
**Phase:** Single phase  
**Wheels:** 8" never flat PVC wheels  
**Spark plug wrench:** Yes



### GD12000E 9500 W

**Rated power:** 8500 W  
**Max power:** 9500 W  
**Displacement:** 688 cc  
**Starting system:** Electric start  
**Oil tank volume:** 1.5 L  
**Fuel tank capacity:** 25 L  
**Low oil sensor:** Yes  
**Excitation type:** Self-excitation  
**Insulation class:** F  
**Phase:** Single phase  
**Spark Plug Wrench:** Yes

### GD12000E-3 10500 W

**Voltage/Frequency:** 380 V~50 Hz  
**Rated power:** 9500 W  
**Max power:** 10500 W  
**Displacement:** 688 cc  
**Starting system:** 12V Electric start  
**Oil tank volume:** 1.5 L  
**Fuel tank capacity:** 25 L  
**Low oil sensor:** Yes  
**Excitation type:** Self-excitation  
**Insulation class:** F  
**Phase:** Three phase  
**Spark Plug Wrench:** Yes

## High Performance

AVR

AVR  
 Automatically maintains constant voltage level



#### Circuit breaker

Or circuit protector in the control panel, which supplies power to the circuit, provides that protection.



#### Oil warning system

When the oil level falls below the lower level, the engine stops automatically.



## Generators



Digital Automatic Voltage Regulator

Voltmeter

AC/DC Protector

Low Oil Alert

Wheels for easy Transportation



### DDAE8000SE 5.0 kW

**Engine type:** Air cooled/Vertical Single Cylinder  
**Rated/Max power:** 4.5 kW / 5.0 kW  
**Displacement:** 418 cc  
**Starting system:** Electric Start  
**Oil tank capacity:** 1.65 L  
**Fuel tank capacity:** 15 L  
**Max noise level at 7 m:** 72-74 dB  
**Run time 50% load:** 13 hs  
**DC Voltage/Current:** 12 V - 20.5 A  
**Tool kit:** Yes

### DDAE8000SE/-3 5.0 kW

**Voltage/Frequency:** 380 V~50 Hz  
**Engine type:** Air cooled/Vertical Single Cylinder  
**Rated/Max power:** 4.5 kW / 5.0 kW  
**Displacement:** 418 cc  
**Starting system:** Electric Start  
**Oil tank capacity:** 1.65 L  
**Fuel tank capacity:** 15 L  
**Max noise level at 7 m:** 72-74 dB  
**Run time 50% load:** 13 hs  
**DC Voltage/Current:** 12 V - 20.5 A  
**Tool Kit:** Yes



SUPER SILENT



DIGITAL DISPLAY

## Super Silent Generator Sse Series



ZERO TURN



SUPER SILENT



DIGITAL DISPLAY



### DDAE9000SSE 5.8 kW

**Engine type:** Air cooled/Vertical Single Cylinder  
**Rated:** 5.5 kW  
**Max power:** 5.8 kW  
**Displacement:** 477 cc  
**Starting system:** Electric Start  
**Oil tank capacity:** 1.65 L  
**Fuel tank capacity:** 15 L  
**Max noise level at 7 m:** 65-68 dB  
**Run time 50% load:** 13 hs  
**DC Voltage/Current:** 12 V - 25 A  
**Tool kit:** Yes

### DDAE9000SSE-3 5.8 kW

**Voltage/Frequency:** 380 V~50 Hz  
**Engine type:** Air cooled/Vertical Single Cylinder  
**Rated:** 5.5 kW  
**Max power:** 5.8 kW  
**Displacement:** 477 cc  
**Starting system:** Electric Start  
**Oil tank capacity:** 1.65 L  
**Fuel tank capacity:** 15 L  
**Max noise level at 7 m:** 65-68 dB  
**Run time 50% load:** 13 hs  
**DC Voltage/Current:** 12 V - 25 A  
**Tool kit:** Yes

### Diesel generators Benefits






Specially designed to be one of the most valuable tools at home or work. From 800 VA to 15 kVA, lack of electricity will not be a problem anymore. Useful to power different kind of applications.

### 8 kW

### DDAE10000DSE/-3

**Voltage/Frequency:** 220-380 V~50 Hz  
**Rated/Max power:** 7.2 kW / 8.0 kW  
**Engine power:** 16 hp  
**Displacement:** 498 cc  
**Starting system:** Electric Start  
**Oil Tank capacity:** 1.65 L  
**Fuel Tank capacity:** 15 L  
**Max noise level at 7 m:** 66 dB  
**Run time 50% load:** 12 hs  
**Tool kit:** Yes



www.famcocorp.com  
 E-mail: info@famcocorp.com  
 @famco\_group

Tel: ۰۲۱-۴۸۰۰۰۰۴۹  
 Fax: ۰۲۱-۴۴۹۹۴۶۴۲



### DDAE10000SE 6.3 kW

**Engine type:** Air cooler/Vertical Single Cylinder  
**Rated/Max power:** 6.0 kW / 6.3 kW  
**Displacement:** 498 cc  
**Starting system:** Electric Start  
**Oil tank capacity:** 1.65 L  
**Fuel tank capacity:** 15 L  
**Max noise level at 7 m:** 72-74 dB  
**Run time 50% load:** 12 hs  
**DC Voltage/Current:** 12 V - 32 A  
**Tool kit:** Yes

### DDAE10000SE-3 6.3 kW

**Voltage/Frequency:** 380 V~50 Hz  
**Engine type:** Air cooler/Vertical Single Cylinder  
**Rated/Max power:** 6.0 kW / 6.3 kW  
**Displacement:** 498 cc  
**Starting system:** Electric Start  
**Oil tank capacity:** 1.65 L  
**Fuel Tank capacity:** 15 L  
**Max noise level at 7 m:** 72-74 dB  
**Run time 50% load:** 12 hs  
**DC Voltage/Current:** 12 V - 32 A  
**Tool Kit:** Yes



ZERO TURN



SUPER SILENT



DIGITAL DISPLAY

Dual Power



We offer the most solid experience in the machinery and power tools market. The complete line of products Daewoo presents an ideal price quality relationship. A high qualified post sales service, complete supply of explosion views and spare parts guarantee the attention of all our customers.

#### SUSTAINABLE PRODUCTION

Our factories are equipped to manufacture worldwide certifiable products, using environmentally safe processes and working continuously to reduce waste.

#### EXCELLENCE IN PRODUCTION

Our team of engineers and designers oversee every detail of our products, from material selection to the ergonomic design for users. Daewoo products are designed for longevity, efficiency and easy use.

#### EXPERT CUSTOMER SERVICE

Our staff provides assistance to customers throughout the purchasing cycle - from initial configuration to the operating instructions and repair service. Customers also have access to our network of service centers and a wide range of spare parts.

#### ONLINE SERVICE

We provide commercial support through products comparison and smart selection tools. Additional services such as access to registration and warranty support are included, ensuring a pleasant experience for our customers.

#### CUSTOMER FRIENDLY

Carefully designed components, attractive packaging and clearly labeled instructions, ensure stress-free experience during the purchase and use of our products.

#### GBR CORPORATION LTD.

Room 03, 16th Floor, Block A,  
China Resources Plaza, Xiejiawan,  
Jiulongpo District, Chongqing, China.  
Ph: (0086) 23 68166136

**INFO@DAEWOOPOWERPRODUCTS.COM**  
**WWW.DAEWOOPOWERPRODUCTS.COM**

[www.famcocorp.com](http://www.famcocorp.com)  
E-mail: [info@famcocorp.com](mailto:info@famcocorp.com)  
@famco\_group

Tel: ۰۲۱-۴۸۰۰۰۰۴۹  
Fax: ۰۲۱-۴۴۹۹۴۶۴۲



# PRODUCTS THAT WILL SOLVE YOUR EVERYDAY NEEDS

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)  
روبروی پالایشگاه نفت پارس، پلاک ۱۲

Tel: ۰۲۱-۴۸۰۰۰۰۴۹  
Fax: ۰۲۱-۴۴۹۹۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)  
روبروی پالایشگاه نفت پارس، پلاک ۱۲

