

Floor scrubber driers

Why disc brush?

Extended mechanical action of the bristles on the floor, ideal for persistent dirt: the special setting of the brush plate allows a balanced gripping effect, assisting easy use in the non traction models. Complete cleaning also next to walls is possible and the compact washing element lower at the sides is studied to scrub also under edges.

How a squeegee should be designed?

The shape and the material used grant a perfect drying in every condition, also on floors with grout or when quick U turns are necessary.

The floating body can stay in the machine operating space (compact/room saving)

The manual adjusting system grants a perfect drying on each kind of floors.

How long do battery charges last?

It is impossible to determine exactly how long a battery charge lasts and so how long a machine can work in autonomy.

Battery autonomy changes depending on type of surface, dirt quantity, brush type and way in which traction system is used (speed and slope).

Battery life is made up of number of charge cycles (also incomplete), if use conditions, charge and service are perfectly observed.

Manufacturing technology diversifies numbers of cycles, service needed, use/charge conditions and performances.



Applications pads



BEIGE PAD - POLISHING - Polyester

To polish all kinds of floor. Use dry.



GREEN PAD - INTERMEDIATE

CLEANING ACTION - Nylon To remove all the old superficial wax, rests, obtaining ready floors to be recoated. Use wet.



BLACK PAD - WET STRIPPING -

Nylon For wet stripping of heavy layers of wax. Ideal to remove old floor finish scu and cement marks.

Walk-behind floor scrubber driers

A1 36



Standard equipment



• 5.511.1346
PPL brush Ø 360 mm - 15"



• 4.508.1100
Front squeegee blade
L.537 mm - Th. 2.5 mm
• 4.508.1101
Rear squeegee blade
L.590 mm - Th. 3 mm



• 0.108.0061
On-board Battery charger
12V 8A
only for model code:
8.518.0007



• 0.107.0061
Maintenance free battery
12V 55Ah BT DC 4.2
only for model code:
8.518.0007



Watch the video on youtube:
www.youtube.com/fasavideo

A1 36

- Suitable to work in high congested areas like small shops, offices, kitchens, schools, hospitals, bars, gyms, restaurants
- Adjustable flow (automatic start-stop with solenoid valve) of the detergent solution depending on type of surface
- Brush with quick release
- Removable recovery tank
- Available in battery version (36B) with integrated battery charger with data memory and for any type of batteries
- Battery included
- Squeegee lifting lever
- Compact reclining handle with control switches
- Easy access and simple service of the components.

	A1 36 E	A1 36 B
Code	8.518.0008	8.518.0007
Power supply	230 V~50 Hz	1 x 12 V
Equipped with	-	Batteries/batt. charger
Scrubbing width	360 mm	360 mm
Squeegee width	460 mm	460 mm
Max working capacity	1260 m ² /h	1260 m ² /h
Detergent tank capacity	11 l.	11 l.
Recovery tank capacity	12/13 l.	12/13 l.
Traction type	mechanical	mechanical

Walk-behind floor scrubber driers



The unit can be supplied mains (15 m cable available) or battery powered. Reclining handle: fit on any operator's height and allowing the perfect cleaning also on 90° corners. Shock-absorbing covers, simple cleaning of the recovery tank, non

marking wheels. Easy access to mechanical parts (easy maintenance of each component), removable recovery tank without tools.



User friendly analogic control panel. Control lever for brush operation and detergent water outflow. General ON/OFF switch, brush and vacuum motor switch, solenoid valve operation switch.

Parabolic squeegee, easy rubber blades replacement. The floating brush plate and squeegee grant the right cleaning pressure on any type of floor.



Optional accessories:



- 0.107.0050 Battery AGM 12V 55Ah C5



- 0.108.0051 Booster battery charger



- 4.508.1058 Polyurethane front blade L.537 TH. 2,5
- 4.508.1059 Polyurethane rear blade L.590 TH. 3



- 5.511.1413 Tynex brush Ø 360 mm-14"
- 5.511.1411 PPL 0,03 brush Ø 360 mm-14"
- 5.511.1412 PES brush Ø 360 mm-14"



- 5.511.1129 EWU pad driver Ø 360mm-14"



- 6.508.0143 Abrasive pad Ø 381 mm-15" - beige (5 pcs.)
- 6.508.0144 Abrasive pad Ø 381 mm-15" - green (5 pcs.)
- 6.508.0141 Abrasive pad Ø 381 mm-15" - black (5 pcs.)



- 4.512.0068 Extension electric cord 15 m with Schuko plug

Walk-behind floor scrubber driers

A3 45



Standard equipment



- 5.511.1688
PPL brush Ø 430 mm - 17"



- 4.508.X468
Front squeegee blade L.830 mm Shore 40 Th. 2.5 mm
- 4.508.X467
Rear squeegee blade L.870 mm Shore 40 Th. 3 mm



- 0.108.0042
On-board Battery charger
CBHD1 24V 10A
only for model code:
8.524.1003
8.524.0003



- 2 x 0.107.0061
Maintenance free battery
12 MFP 50 - 12V 50Ah
only for model code:
8.524.0003

Other available versions:

- 8.524.1003 - A3 45 B without batteries



Watch the video on youtube:
www.youtube.com/fasavideo

A3 45

- Suitable to work in high congested areas like wellness centres and medical environments in general, gyms, retail outlets, car shops, sales points and health care
- Solution water filter and solenoid valve (battery model only)
- User friendly control panel
- Hour meter (optional)
- Chemical dosing system on request
- Recovery water tank with visual inspection
- Reclining handle with control lever (battery model only)
- Low noise operation thanks to the protected positioning of vacuum motor
- Recovery tank drain hose with adjustable flow system
- Indicator of the solution water tank fill level
- Easy access to the recovery tank
- Non-marking wheels.

	A3 45 E	A3 45 B
Code	8.524.3303	8.524.0003
Power supply	230V~50Hz	24V DC
Equipped with	-	Batteries/batt. charger
Scrubbing width	450 mm	450 mm
Squeegee width	800 mm	800 mm
Max working capacity	1575 m2/h	1575 m2/h
Detergent tank capacity	25 l.	25 l.
Recovery tank capacity	25-28 l.	25-28 l.
Traction type	mechanical	mechanical

Walk-behind floor scrubber driers



User friendly analogic control panel. Control lever for brush operation and detergent water outflow. ON/OFF and battery cutout key switch, brush and vacuum motor switch, detergent dosing knob (optional), Thermal circuit breaker to protect

vacuum and brush motor, battery level indicator, hour meter (optional). Automatic detergent dosing system on request. Indicator of clean water tank level. Detergent solution regulation. Recovery tank drain hose with adjustable



flow system. Easy access to recovery water tank with visual inspection. Extremely silent (62 dB) thanks to the particular housing of the vacuum motor and the use of soundproofing material.

Thanks to the special squeegee support it is easily possible the tilting of the machine to carry out the drying of the floor without scrubbing. The oversize wheels facilitate maneuverability and effortless use.



Optional accessories:



- 0.107.0050
Battery AGM
12V 55Ah C5



- 4.508.1178 Polyurethane front blade L.830 TH. 3
- 4.508.1177 Polyurethane rear blade L.870 TH. 4



- 5.511.1713 Tynex brush Ø 430 mm-17"
- 5.511.1711 PPL 0,03 brush Ø 430 mm-17"
- 5.511.1712 PES brush Ø 430 mm - 17"



- 5.511.1095
EWU pad driver Ø 430 mm-17"



- 6.508.0032 Abrasive pad Ø 430 mm-17" - beige (5 pcs.)
- 6.508.0039 Abrasive pad Ø 430 mm-17" - green (5 pcs.)
- 6.508.0046 Abrasive pad Ø 430 mm-17" - black (5 pcs.)



- 4.512.0068
Extension electric cord 15 m with Schuko plug

- 5.511.1687 Automatic detergent dosing system on request.

Walk-behind floor scrubber driers

A4 45



Standard equipment



• 5.511.1941
Brosse PPL Ø 430 mm - 17"



• 4.508.1319 Front squeegee blade Shore 40 Th.
• 4.508.1320 Rear squeegee blade Shore 40 Th.



• 0.108.0073
On-board Battery charger
24V 10A
(only for model code:
8.580.0005/8.580.0006)



• 2 x 0.107.0061
Maintenance free battery
12 MFP 50 - 12V 50Ah
only for model code:
8.580.0006



Watch the video on youtube:
www.youtube.com/fasavideo

A4 45

- Ideal for small and medium floors up to 1600sqm, especially when congested by people or furnishing like in wellness centres, gyms, car showroom, retail shops, hospitals and schools.
- Automatic brush attachment, discharge and delayed cut-off.
- Adjustable solution release with automatic cut-off.
- Narrow body with both side brush protrusion and 300° squeegee spin.
- Tool less removable recovery tank with large visual inspection window and stretchable discharge hose.
- Adjustable driving handle with dead man switches, soft touch controls and diagnosis (Eco Energy mode and battery low level automatic cut-off for DC version).
- Large non marking working wheels and sturdy rear

	A4 45E	A4 45 B	A3 45 B
Code	8.580.0004	8.580.0005	8.580.0006
Power supply	230V~50Hz	24V DC	24V DC
Equipped with	-	Batt. charger	Batteries/batt. charger
Scrubbing width	450 mm	450 mm	450 mm
Squeegee width	540 mm	540 mm	540 mm
Max working capacity	1575 m2/h	1575 m2/h	1575 m2/h
Detergent tank capacity	30 l.	30 l.	30 l.
Recovery tank capacity	32-35 l.	32-35 l.	32-35 l.
Traction type	mechanical	mechanical	mechanical

Walk-behind floor scrubber driers



Protection against overloads, battery discharge abuse (DC only) and undesired run. Convenient one switch maintenance over the brush. Eco Energy setting for extensive working time and extremely quiet operations (DC only). Accessible on-

board charger (DC only, when provided), far away from sprays. Time saving convenient foot operating squeegee lift. Handle can be easily adjusted to fit comfort of operators even in narrow spaces. Easy access and handling to clean recovery tank and



floater. Less downtimes due to simple maintenance and construction. Great visibility and cleaning capability on hard to reach edges on both sides of the brush. Extensive squeegee spin for easy blade replacement and perfect suction even on corners

Easy setting and automatic solution release to save chemical and fit different floor conditions. High stability and capability to overtake small steps.



Optional accessories:



- 0.107.0050 Battery AGM 12V 55Ah



- 4.508.1324 Polyurethane front blade TH. 3
- 4.508.1325 Polyurethane rear blade TH. 4



- 5.511.1942 Tynex brush Ø 430 mm-17"
- 5.511.1943 PP 0,03 brush Ø 430 mm-17"
- 5.511.1944 PES brush Ø 430 mm - 17"



- 5.511.0229 EWU pad driver Ø 430 mm-17"



- 6.508.0032 Abrasive pad Ø 430 mm-17" - beige (5 pcs.)
- 6.508.0039 Abrasive pad Ø 430 mm-17" - green (5 pcs.)
- 6.508.0046 Abrasive pad Ø 430 mm-17" - black (5 pcs.)



- 4.512.0068 Extension electric cord 15 m with Schuko plug

Walk-behind floor scrubber driers

A5 EVO 50



Standard equipment



- 5.511.1097
PPL brush Ø 483 mm - 19"



- 4.508.X468
Front squeegee blade L.830 mm Shore 40 Th. 2.5 mm
- 4.508.X467
Rear squeegee blade L.870 mm Shore 40 Th. 3 mm



- 0.108.0042
On-board Battery charger
CBHD1 24V 10A
only for model code:
8.527.0007 - 8.527.0008
8.527.0013 - 8.527.0046



- 0.107.0054
Maintenance free battery
12V 75Ah BT DC 5.5
only for model code:
8.527.0013 - 8.527.0046

Other available versions:

- 8.527.0007- A5 Evo 50 B with battery charger
- 8.527.0013 - A5 Evo 50 B with batteries and battery charger
- 8.527.0046 - A5 Evo 50 BT with batteries and battery charger with traction.



Watch the video on youtube:
www.youtube.com/fasavideo

A5 EVO 50

- Very compact scrubbing machines suitable to work for the maintenance cleaning of limited-size areas (up to 1.500 m²)
- Especially suitable for cleaning: car shops, sales points, gym, health care
- Control panel with operator presence safety system
- Low level battery indicator: brush/vacuum and traction progressive cut off
- Solution water filter and solenoid valve (battery model only)
- Easy access to the battery compartment
- Quick drain and easily inspectable recovery tank
- Non-marking wheels
- Roto-molded polyethylene tanks, shock and acid resistant
- The lower tank also serves as battery compartment
- Low noise operation thanks to the protected positioning of vacuum motor.

	A5 EVO 50 E	A5 EVO 50 B	A5 EVO 50 BT
Code	8.527.0005	8.527.0006	8.527.0008*
Power supply	230V~50Hz	24V DC	24V DC
Equipped with	-	-	Batt. charger
Scrubbing width	500 mm	500 mm	500 mm
Squeegee width	800 mm	800 mm	800 mm
Max working capacity	2000 m²/h	2000 m²/h	2000 m²/h
Detergent tank capacity	44 l.	44 l.	44 l.
Recovery tank capacity	50/60 l.	50/60 l.	50/60 l.
Traction type	mechanical	mechanical	automatic

Walk-behind floor scrubber driers



Powerful gearmotor; metal brush plate with integrated plastic splash guard/ bumper.

The outflow of the detergent solution is controlled by a solenoid valve. The actuation of the solenoid valve is operated by the control lever, avoiding the detergent solution outflow when the brush is stopped during the interruptions of work.



Renovated squeegee with new pressure adjusting system. The squeegee blades are easily replaceable without the use of tools. Quick and easy squeegee coupling through the two large knobs; the squeegee is released without any damage in the

event of accidental impact. Easy and intuitive controls. The outflow of the cleaning solution is easily controlled using the mechanical lever placed on the control panel. Inspectable mesh filter to trap any existing solid body in the cleaning



Optional accessories:



- 2 x 0.107.0002
Tubular battery Pb-acid
12V 118Ah C5



- 2 x 0.107.0063
GEL Battery 12 MFP 105
12V 105Ah C5



- 4.508.1178 Polyurethane
front blade L.830 TH. 3
- 4.508.1177 Polyurethane
rear blade L.870 TH. 4



- 5.511.1098
Tynex brush Ø 483 mm-19"
- 5.511.1128
PPL 0,03 brush Ø 483 mm-19"
- 5.511.1206
PES brush Ø 483 mm - 19"



- 5.511.1099
EWU pad driver Ø 483
mm-19"



- 6.508.0034
Abrasive pad Ø 483 mm-19"
- beige (5 pcs.)
- 6.508.0041
Abrasive pad Ø 483 mm-19"
- green (5 pcs.)
- 6.508.0048
Abrasive pad Ø 483 mm-19"
- black (5 pcs.)



- 4.512.0068
Extension electric cord 15 m
with Schuko plug

Walk-behind floor scrubber driers

A8 EVO 66



Standard equipment



- 2 x 5.511.1105
PPL brush Ø 330 mm - 13"



- 4.508.1524
Front squeegee blade L.860 mm
Shore 33 Th. 4 mm
- 4.508.1523
Rear squeegee blade L.900 mm
Shore 40 Th. 4 mm



- 0.108.0059
On-board Battery charger
CBHD1-XR 24V 12A



Watch the video on youtube:
www.youtube.com/fasavideo



A8 Evo 66

- Designed for the maintenance and deep cleaning of large areas (up to 1.700 m²)
- Especially suitable for cleaning: car shops, sales points, gym, health care • User friendly control panel • Automatic brush lifting • Fully accessible recovery water tank with visual inspection • Automatic detergent measuring system • Big size traction wheels • Handle with control lever

A8 EVO 66 BTA

Code	8.525.1303
Power supply	24V DC
Equipped with	Batt. charger
Scrubbing width	660 mm
Squeegee width	800 mm
Max working capacity	2640 m ² /h
Detergent tank capacity	55 l.
Recovery tank capacity	55/65 l.
Traction type	200W/automatic

Walk-behind floor scrubber driers



User friendly analogic control panel. Control lever for brush operation and detergent water outflow. ON/OFF and battery cutout key switch, brush and vacuum motor switch, detergent regulation device (optional). Thermal circuit breaker to protect

vacuum motor and brush motor, battery charge level indicator, hour meter. Clean water tank level indicator. Detergent regulation device. Recovery tank drain hose with adjustable flow system. Automatic brush lifting



Automatic detergent dosing system (only model 66TA). Fully accessible recovery water tank with visual inspection. Easy access to the recovery tank. Easy access and simple service of the components without use of tools.



Battery trolley for a quick and easy battery change. Big size wheels for better maneuverability and effortless use.



Optional accessories:



- 2 x 0.107.0002
Tubular battery Pb-acid
12V 118Ah C5



- 2 x 0.107.0063
GEL Battery 12 MFP 105
12V 105Ah C5



- 0.108.0001
Battery Charger 24V 12A
220-240/50-60



- 5.511.1494
On-board Battery charger
kit - 24V - 12A



- 4.508.1526 Polyurethane
front blade L.860 TH. 4
- 4.508.1525 Polyurethane
rear blade L.900 TH. 4



- 2 x 5.511.1106
Tynex brush Ø 330 mm-13"
- 2 x 5.511.1255
PPL 0,03 brush Ø 330 mm-13"
- 2 x 5.511.1202
PES brush Ø 330 mm-13"



- 2 x 5.511.1107
EWU pad driver Ø 330mm-13"



- 6.508.0030 - Ø 340 mm-
13"- beige (5 pcs.)
- 6.508.0037 - Ø 340 mm-
13"- green (5 pcs.)
- 6.508.0044 - Ø 340 mm-
13"- black (5 pcs.)

Walk-behind floor scrubber driers

A9



Standard equipment



A9 50T

- 5.511.1097
PPL brush Ø 483 mm - 19"



A9 55T

- 2 x 5.511.1101
PPL brush Ø 275 mm - 10"



A9 66T

- 2 x 5.511.1105
PPL brush Ø 330 mm - 13"



- 4.508.X468
Front squeegee blade L.830 mm
Shore 40 Th. 2.5 mm
- 4.508.X467
Rear squeegee blade L.870 mm
Shore 40 Th. 3 mm



Watch the video on youtube:
www.youtube.com/fasavideo

A9

- Suitable to work for the maintenance and deep cleaning of large areas (up to 2.200 m²)
- User friendly control panel: forward speed setting, scrubbing and vacuuming selectors, battery charge indicator, traction direction indicator, key main switch • Large handle with traction driving lever for forward and backward directions • Self levelling brush plate • Cover removable without tools provided with self locking system • Quick vacuum motor and filter inspection, without tools • Detergent solution tank with large opening protected by quick locking cap • Parking brake directly on the wheel • Non-marking wheels • Easy squeegee regulation without tools • Movable shock-proof

	A9 50 BT	A9 55 BT	A9 66 BT
Code	8.516.0413	8.516.0414	8.516.0424
Power supply	24V DC	24V DC	24V DC
Equipped with	-	-	-
Scrubbing width	500 mm	550 mm	660 mm
Squeegee width	800 mm	800 mm	800 mm
Max working capacity	2250 m ² /h	2475 m ² /h	2970 m ² /h
Detergent tank capacity	67 l.	67 l.	67 l.
Recovery tank capacity	77/95 l.	77/95 l.	77/95 l.
Traction type	200W/automatic	200W/automatic	200W/automatic

Walk-behind floor scrubber driers



User friendly control panel. Speed adjustment selectors. General ON/OFF and key switch, brush and vacuum motor switch. Thermal circuit breaker to protect vacuum motor and brush motor, battery level control, hour meter.

Easy access to battery and vacuum motor compartment, without using tools. Large tank capacity, at the top in the category (67 l). 2 x 12V - 118 Ah C5 batteries to grant long work autonomy, up to 3 hours.



Control lever for brush operation and detergent water outflow. Recovery tank drain hose. Quick fitting battery charger plug.

Heavy duty 15 mm steel monobloc brush plate. Great pressure on the floor for a deep cleaning even on the toughest dirt. Self levelling system. Solenoid valve to stop the detergent water outflow during the work interruptions.



Optional accessories:



• 2 x 0.107.0002
Tubular battery Pb-acid
12V 118Ah C5



• 2 x 0.107.0063
GEL Battery 12 MFP 105
12V 105Ah C5



• 0.108.0001
Battery Charger 24V 25A
220-240/50-60



• 5.511.1494
On-board Battery charger
kit - 24V - 12A



• 4.508.1178 Polyurethane
front blade L.830 TH. 3
• 4.508.1177 Polyurethane
rear blade L.870 TH. 4



• 5.511.1098
Tynex brush Ø 483 mm-19"
• 2 x 5.511.1102
Tynex brush Ø 275 mm-10"
• 2 x 5.511.1106
Tynex brush Ø 330 mm-13"

• 5.511.1128
PPL 0,03 brush Ø 483 mm-19"
• 2 x 5.511.1254
PPL 0,03 brush Ø 275 mm-10"
• 2 x 5.511.1255
PPL 0,03 brush Ø 330 mm-13"

• 5.511.1206
PES brush Ø 483 mm - 19"
• 2 x 5.511.1201
PES brush Ø 275 mm-10"
• 2 x 5.511.1202
PES brush Ø 330 mm-13"



• 5.511.1099
EWU pad driver Ø 483mm-19"
• 2 x 5.511.1103
EWU pad driver Ø 275mm-10"
• 2 x 5.511.1107
EWU pad driver Ø 330mm-13"



(5 pcs package)

• 6.508.0034 - Ø 483 mm-19"- beige
• 6.508.0041 - Ø 483 mm-19"- green
• 6.508.0048 - Ø 483 mm-19"- black

• 6.508.0095 - Ø 280 mm-11"- beige
• 6.508.0096 - Ø 280 mm-11"- green
• 6.508.0097 - Ø 280 mm-11"- black

• 6.508.0030 - Ø 340 mm-13"- beige
• 6.508.0037 - Ø 340 mm-13"- green

Walk-behind floor scrubber driers

A12 75



Standard equipment

A12 75T



- 2 x 5.511.1168
PPL brush Ø 360 mm - 14"



- 4.508.0646
Front squeegee blade L.925 mm
Shore 40 Th. 3 mm
- 4.508.0605
Rear squeegee blade L.1015 mm
Shore 30 Th. 4 mm



Watch the video on youtube:
www.youtube.com/fasavideo

A12

- Capable to work for the maintenance and deep cleaning of large areas (up to 2.600 m²)
- User friendly control panel: forward speed setting, scrubbing and vacuuming selectors, battery charge indicator, traction direction indicator, key main switch • Large handle with traction driving lever for forward and backward directions • Self levelling brush plate • Cover removable without tools • Quick vacuum motor and filter inspection, without tools • Detergent solution filter • Detergent solution tank provided with large opening protected by quick locking cap.

A12 75 BT

Code	8.517.0106
Power supply	24V DC
Equipped with	-
Scrubbing width	750 mm
Squeegee width	900 mm
Max working capacity	4275 m ² /h
Detergent tank capacity	88 l.
Recovery tank capacity	91/95 l.
Traction type	300W/automatic

Walk-behind floor scrubber driers



Easy access to battery and vacuum motor compartment, without using tools. Large capacity shock and acid proof polyethylene tanks (88 l) avoid frequent refilling and idle time. 4 x 6V -180 Ah C5 batteries

granting continuous working time up to 4-5 hours. Adjustable speed ensures high precision in cleaning congested areas with obstacles. Intuitive controls reduce operator's training time. Safety thermal breakers prevent motor problems



in case of overheating or operator's misuse. Heavy duty V-shaped squeegee ensures perfect drying of every type of floor, even with large joints. Non-marking wheels avoid marks after the drying. Completely adjustable to fit any surface.

Strong mechanical control levers for heavy duty use. Large size drain hose for a fast emptying and a better cleaning of the recovery tank. Quick fitting battery charger plug.



Optional accessories:



- 4 x 0.107.0004
Tubular battery Pb-acid
6V 180Ah C5



- 4 x 0.107.0072
GEL Battery 6 MFP 180
6V 180Ah C5



- 0.108.0002
Battery Charger 24V 25A
220-240/50-60
- 5.511.1495
On-board Battery charger
kit - 24V - 25A



- 4.508.0901 Polyurethane
front blade L.925 TH.3 Sh.40
- 4.508.0900 Polyurethane
rear blade L.1015 TH.4 Sh.40



- 2 x 5.511.1246
Tynex brush Ø 360 mm-14"
- 2 x 5.511.1169
PPL 0,03 brush Ø 360 mm-14"
- 2 x 5.511.1203
PES brush Ø 360 mm - 14"



- 2 x 5.511.1129
EWU pad driver Ø 360 mm-14"



(5 pcs package)

- 6.508.0030 - Ø 340 mm-13"- beige
- 6.508.0037 - Ø 340 mm-13"- green
- 6.508.0044 - Ø 340 mm-13"- black
- 6.508.0143 - Ø 380 mm-15"- beige
- 6.508.0144 - Ø 380 mm-15"- green
- 6.508.0141 - Ø 380 mm-15"- black