



TFDA Registered
NO.007320

TES-3280 IR Forehead Thermometer

Product Features

- TFDA Registered NO.007320
- Forehead Temperature, Room Temperature, Surface Temperature measurement
- Applicable to Shops, Restaurants, Institutions, Schools and Homes
- Light and handy, Large LCD, easy to read
- Quick and accurate for Indoor and Outdoor measurement
- Fever warning function: Green, Orange and Red 3 color screen display
- LED light spot measurement and positioning

SPECIFICATIONS

Display	Backlight LCD display
Measurement range	Body temperature (Forehead temperature) mode: 34°C to 42°C (93.2°F to 107.6°F) Surface temperature mode: 0°C to 100°C (32°F to 212°F) Room temperature mode: 16°C to 40°C (60°F to 104°F)
Resolution	0.1°C/0.2°F
Accuracy	22°C to 42°C (±0.3°C) / 71.6°F to 107.6°F (±0.5°F) <22°C to 0°C (±1°C) / <71.6°F to 32°F (±1.8°F) >42°C to 100°C (±1°C) / >107.6°F to 212°F (±1.8°F)
Spectral response	6 to 14μm
Measuring distance	1 to 5 cm
Sighting	LED point indication: Auto-off


GENERAL SPECIFICATIONS

Auto power off	Approx. 60 sec
Battery life	Continuous use approx. 30 hours (LED point and backlight aren't on use)
Power source	9V Battery
Operating condition	15°C to 40°C (59°F to 104°F) below 95%RH (non-condensation)
Storage condition	-20°C to 50°C (-4°F to 122°F) below 95%RH (non-condensation)
Dimensions	175mm x 118mm x 50mm
Weight	Approx. 200g
Accessories	Instruction manual, Battery and Storage bag

شرکت سائن

WWW.SAENCO.COM

021 88936611



www.famcocorp.com

E-mail: info@famcocorp.com

@famco_group

Tel: ۰۲۱-۴۸۰۰۰۰۴۹

Fax: ۰۲۱-۴۴۹۹۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

روبروی پالایشگاه نفت پارس، پلاک ۱۲

TES

Reliable in Quality

TES-1327K IR Thermometer

- Dual Thermometer & Dual Display
- Emissivity Adjustable
- Audible and Visible Alarm
- Logging Function



TES-1326



TES-1327



TES-1327K

Range:
IR: -35°C~500°C

www.famcocorp.com

E-mail: info@famcocorp.com

@famco_group

Tel: ۰۲۱-۴۸۰۰۰۰۴۹

Fax: ۰۲۱-۴۴۹۹۴۶۴۲

تهران، کیلومتر ۲۱ بزرگراه لشگری (جاده مخصوص کرج)

و بروی پالایشگاه نفت پارس، پلاک ۱۲

TES 1326 / 1327 / 1327K Infrared / Type-K Thermometer

FEATURES :

- °C / °F Selectable.
- Back-light LCD display.
- Laser targeting.
- Maximum / Minimum function.
- Dual thermometer and dual display. (1327K)
- Emissivity adjustable. (1327/1327K)
- Audible and visible alarm. (1327/1327K)
- Data memory and read function. (1327/1327K)

INFRARED THERMOMETER :

Display	Backlight LCD display
Measurement Range	-35°C ~ 500°C (-4°F ~ 932°F)
Resolution	0.1°C / 0.2°F
Accuracy	±2% reading or ±2°C
Spectral Response	6 ~ 14μm
Field of View	10:1 optics ratio with a 1" min target
Emissivity	0.17 ~ 1.00 , (1326 : fixed 0.95)
Sighting	Laser marker < 1mw

K-TYPE THERMOMETER (for 1327K) :

Measurement Range	-150°C ~ 1350°C (-238°F ~ 1999°F)			
Resolution	0.1°C / 1°C , 0.1°F / 1°F			
	Function	Resolution	Range	Accuracy
	°C	0.1°C	-150°C ~ 0°C	±(0.2%rdg + 1.0°C)
			0°C ~ 200°C	±(0.1%rdg + 1.0°C)
	°F	0.1°F	200°C ~ 1350°C	±(0.2%rdg + 2°C)
			-238°F ~ 32°F	±(0.2%rdg + 2°F)
			32°F ~ 200°F	±(0.1%rdg + 2°F)
		1°F	200°F ~ 1999°F	±(0.2%rdg + 4°F)

GENERAL SPECIFICATIONS :

Data memory capacity	50 sets (Direct reading from LCD display) (1327/1327K)
Auto power off	approx. 15 sec
Battery Life	Approx. 100 hours (laser pointer and backlight aren't on use) (Alkaline)
Power Source	One 9V cell (ANSI/NEDA-1604A, IEC-6LR61)
Operating / Storage Condition	0°C ~ 50°C (32°F ~ 122°F) below 80%RH -10°C ~ 60°C (14°F ~ 140°F) below 7 %RH
Dimensions	172mm x 118mm x 46mm
Weight	220g
Accessories	Instruction manual, Battery

TES

TES ELECTRICAL ELECTRONIC CORP.

7F, No.31 Lane 513, Rui Guang Rd., Neihu Dist, Taipei , Taiwan

www.famcocorp.com

E-mail: info@famcocorp.com

@famco_group

Tel: 021- 4 8 0 0 0 0 4 9

Fax: 021 - 4 4 9 9 4 6 4 2

سوس کرج

شرکت سانن

WWW.SAENCO.COM

021 88936611

