

SPECIFICATIONS

	Range	UT361	UT362
Wind speed measurement	2m/s~10m/s	±(3%+0.5)	±(3%+0.5)
	10m/s~30m/s	±(3%+0.8)	±(3%+0.8)
Wind count measurement (CMM)	0.001~9999 x 100	√	√
Wind count measurement (CFM)	0.001~9999 x 100	√	√
Temperature measurement	0°C~40°C (32°F~104°F)	±3°C (±4°F)	±3°C (±4°F)
Features			
Display count		10000	10000
Data hold		√	√
Auto power off	Around 10 minutes	√	√
Low battery indication	≤7.2V	√	√
MAX/MIN mode		√	√
Data storage		2044	2044
USB interface			√
Auto record time setup		√	√
Units switch		√	√
LCD backlight		√	√
Wind speed display	Display "VEL"	√	√
Wind count display	Display "FLOW"	√	√



● UT362

UT360 series anemometers can measure temperature, wind speed, and wind count. These meters can be used in energy saving, HVAC, fishing and other industries that use exhaust or ventilation systems.

GENERAL CHARACTERISTICS

Power	9V battery (6F22)
Display	57mm x 37mm
Product color	Red and grey
Product net weight	375g
Product size	162mm x 78mm x 30mm
Standard accessories	Battery, USB interface cable (UT362), PC software CD (UT362), carrying bag
Standard individual packing	Gift box, English manual
Standard quantity per carton	10pcs
Standard carton measurement	460mm x 335mm x 210mm
Standard carton gross weight	6.8kg



SPECIFICATIONS

	UT363	UT363BT
Wind speed	0~30m/s	0~30m/s
Wind speed accuracy	±(5%rdg+0.5)	±(5%rdg+0.5)
Wind speed resolution	0.1m/s	0.1m/s
Temperature	-10~50°C	-10~50°C
	14~122°F	14~122°F
Temperature accuracy	±2°C/±4°F	±2°C/±4°F
Temperature resolution	0.1°C/0.2°F	0.1°C/0.2°F
Wind scale	Level 0~12	Level 0~12
Wind scale accuracy	±1	±1
Sampling rate	0.5s	0.5s
Features		
APP		√
Bluetooth®		√
Overload indication (>45m/s)	OL	OL
MAX/AVG	√	√
Data hold	√	√
LCD backlight	√	√
Auto power off	5 min	5 min
Low battery indication	3V~3.5V	3V~3.5V



● UT363 BT

GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 3
Display	32mm x 26mm
Product color	Red and grey
Product net weight	118g
Product size	160mm x 50mm x 28mm
Standard accessories	Batteries
Standard individual packing	Blister, English manual
Standard quantity per carton	UT363: 40pcs; UT363 BT: 20pcs
Standard carton measurement	UT363: 505mm x 330mm x 280mm UT363 BT: 332mm x 262mm x 290mm
Standard carton gross weight	UT363: 8.42kg; UT363 BT: 4.2kg



UT363/UT363BT are mini wind speed and temperature meters. UT363 and UT363BT can measure wind speeds up to 30m/s and 45m/s respectively. UT363BT can transfer measurement data through bluetooth to UNI-T's custom mobile APP (iENV) for further analysis, storage, and export. iENV can be downloaded from Google Play, Apple Store or UNI-T's website by searching 'iENV'.

UT363S Digital Anemometer

UT363S is a stable, safe and reliable split-type anemometer, featuring quick detection, low consumption and high accuracy. It can be widely used in mining, electric, iron and steel, petrochemical, energy-saving, navigation, fan manufacturing, exhaust ventilation, sporting and more sectors.



SPECIFICATIONS

	Range	Resolution	Accuracy
Wind speed	0.4~30m/s	0~99: 0.01	±(5%+0.5m/s)
	1.4~108km/h		±(5%+1.5km/h)
	78~5905ft/min	100~999: 0.1	±(5%+100ft/min)
	0.7~58knots	≥1000: 1	±(5%+1knots)
	0.8~67mph		±(5%+1mph)
Temperature	-10~50°C	0.1°C	±2.0°C
	14~122°F	0.2°F	±4.0°F
Wind scale	0~12	1	±1

Features

Sampling rate	0.5s
Units	m/s, km/h, ft/min, knots, mph, °C/°F
Overload indication	√
Auto range	√
Auto power off	√
Low battery indication	√
Data hold	√
MAX/MIN/AVG	√
Backlight	√
Working temperature	0°C~40°C
1m drop test	√

GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 3
Display	35mm x 32mm
Product color	Red and grey
Product net weight	365g
Product size	120mm x 53mm x 43mm
Standard accessories	Batteries
Standard individual packing	Gift box, blister, English manual
Standard quantity per carton	20pcs
Standard carton measurement	550mm x 295mm x 350mm